

42265 & 42275 Humidity and Temperature Datalogger Kits



Compact, powerful and easy-to-use dataloggers record up to 16,000 readings. Models to choose from: Temperature (42260/42265) or Temperature and Relative Humidity Datalogger (42270/42275). Multiple Dataloggers can be programmed and data downloaded from one single docking station. USB cable and software included to easily download collected data to your PC for further analysis.

Applications:

- Clean rooms
- Freezer
- Shipping crates
- Storage areas
- Refrigerator
- Shipping vans
- Cargo vessels
- Warehouses



Features

- **Model 42265** — Temperature Datalogger kit records up to 8000 readings
- **Model 42275** — Temperature and Humidity Datalogger kit records up to 16,000 readings
- Use in storage containers, shipping vans, and freezers
- Logs data for days, weeks or months (~1yr battery life)
- Multiple Dataloggers (42260 or 42270) can be programmed and data downloaded from one single docking station
- Programmable sampling rate from 1 sec to 2hrs plus Hi/Lo limits with alarm indication
- Program the logger, analyze and store data using Windows[®] XP, Win 7, Win 8 compatible software
- View temperature (42265) or both humidity and temperature (42275) on LCD display
- Three start methods: Scheduled, immediate, magnetic
- Real time clock stores date & time with data
- Waterproof: 42260 to IP65, Water-resistant: 42270
- Kits include one datalogger, docking station with USB cable, and software

Specifications	Range	Max Resolution	Basic Accuracy
Temperature	-40°F to 185°F (-40°C to 85°C)	0.1°	±1°F/ ±0.6°C
Humidity	0 to 100%RH	0.1%	±3%RH
Datalogging Interval	1 sec to 12 hours		
Memory	42260/42265: Temperature: 8000 points; 42270/42275: Temperature: 8000 points and Relative Humidity: 8000 points		
Dimensions	42260 or 42270: 3 x 2.3 x 0.88" (76 x 57.2 x 22.3mm); 42265 or 42275: 4.9 x 3.8 x 2" (123.8 x 95.3 x 51mm)		
Weight	42260 or 42270: 2.6oz. (72.6g), 42265 or 42275: 9oz (254g)		

Ordering

(NOTE: Order model 42270 or 42260, Datalogger only, as a replacement unit or as an addition to the kit. The datalogger by itself cannot function without the software and docking station)

- 42275..... Temperature/Humidity Datalogger Kit with PC Interface
- 42270..... Temperature/Humidity Datalogger for 42275
- 42265..... Temperature Datalogger Kit with PC Interface
- 42260..... Temperature Datalogger for 42265
- 42299..... Replacement 3.6V Lithium batteries (2pk)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)