

309-65234



**Article Number:** 309-65234

**Heat Shrink Tubing, 4FT-Stick, 2:1, 4.0", 102/50.8 dia., Polyolefin, White, 2/pkg**



## Base Data

**Local Order Number** 309-65234

**Type** TFN21-ST 102/50.8 WH

**Color** White (WH)

- Features and Benefits**
- Thin, 2 to 1 shrink ratio tubing provides insulation and abrasion protection for wires and cables.
  - Flammability rating of UL224 VW-1 for use in applications requiring the highest degree of flame protection (excludes clear tubing).
  - Flexible-yet-durable material resists most common oils, chemicals and fluids.
  - Available in a variety of diameters and colors for identifying and marking wires and cables.
  - Available in mini reels, bulk reels, and sticks for small to large volume applications.

**Product Description** TFN21 is a highly flexible thin wall heat shrink tubing with a 2 to 1 shrink ratio and excellent flame retardant properties. In addition to providing insulation and abrasion protection for wires and cables, the polyolefin material also offers resistance to oils, solvents and chemicals. Available in mini reels, bulk reels and sticks, for small to large volume applications.

**Short Description** Heat Shrink Tubing, 4FT-Stick, 2:1, 4.0", 102/50.8 dia., Polyolefin, White, 2/pkg

## Product Dimensions

**Length L2 (Imperial)** 4.0 ft

**Length L2 (Metric)** 1.22 m

**Printable (Yes/No)** Yes

**Shrink Ratio** 2:1

**Tensile Strength (MPa)** 14 MPa

**Trade Size** 4 "

**Variant** Thin-Wall

**Volume Resistance (Ohm cm)** 10<sup>11</sup> Ω cm

**Nominal Diameter (Imperial)** 4 "

**Nominal Diameter (Metric)** 102 mm

**Wall Thickness WT (Imperial)** .053 "

**Wall Thickness WT (Metric)** 1.35 mm

**Recovered Diameter d (metric)** 50.8 mm

**Recovered Diameter d (imperial)** 2.0 "

**Supplied Diameter D (metric)** 102 mm

**Supplied Diameter D (imperial)** 4.0 "

## Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 2

## Material and Specifications

---

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Material</b>                     | Polyolefin, cross-linked (PO-X)   |
| <b>Material Shortcut</b>            | PO-X                              |
| <b>Dielectric Strength (Metric)</b> | 20 kV/mm                          |
| <b>Elongation at break</b>          | 600%                              |
| <b>Flammability</b>                 | UL224 VW-1                        |
| <b>Halogenfree</b>                  | No                                |
| <b>Shrink Temperature</b>           | +212 °F (+100 °C)                 |
| <b>Operating Temperature</b>        | -67°F to +275°F (-55°C to +135°C) |
| <b>ROHS Compliant</b>               | Yes                               |
| <b>Certification/Specification</b>  | CSA<br>UL224 125 °C 600V VW-1     |
| <b>UL Recognized (US)</b>           | Yes                               |

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-007A303](#)  
[770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-NO.65-X-SP](#)  
[MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#)  
[MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-](#)  
[1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-](#)  
[316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#) [121-](#)  
[123-1-1-40BTC](#) [121-127-09BK](#)