SlimLine spanners. Hands-on tools. CrV steel drop forged, carefully hardened and pla



- Optimal surface protection by means of double nickel-plating and single chrome-plating. With easy to hold, smooth finish.
- With durable laser inscribed and clearly readable sizes in mm.
- Polished heads: slim and thin walled. Torque characteristics still exceed DIN/ISO requirements.
 - Dimensional tolerances are better than those required by DIN/ISO. Each piece is calibrated and checked.

8-piece SlimLine - **open-end spanner set**, including holder. To DIN 3110 and ISO 3318.

Includes 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19 and 20 x 22mm. Supplied with a plastic holder with slot for each spanner and holes for attaching to a wall. All spanners clearly labelled to make them easy to find.

NO 23 800 set

+						
B ₁ S ₁						
H						
PROXMON	<u>.</u>					
INDUSTRIAL		SlimLine-open-end spanners, individually				
	s ₁ x s ₂	^B 1	^B 2	L	н	
23 828	5 x 5.5 mm	13	14	111	3	
23 830	6 x 7 mm	16	18	123	3.4	
23 832	8 x 9 mm	20	22	140	3.5	
23 834	10 x 11 mm	24	26	157	4.5	
23 836	12 x 13 mm	28	29	173	4.7	
23 838	10 x 13 mm	24	29	174	4.7	
23 840	14 x 15 mm	32	34	190	5.5	
23 842	16 x 17 mm	36	38	205	6	
23 846	18 x 19 mm	38	42	220	6.5	
23 848	17 x 19 mm	38	42	220	6.5	
23 850	20 x 22 mm	43	46	235	7.5	
23 852	21 x 23 mm	45	48	248	7.5	
23 856	24 x 27 mm	49	55	268	8.5	
23 860	30 x 32 mm	59	64	302	9.5	
23 864	34 x 36 mm	65	79	320	10	
23 866	41 x 46 mm	86	95	415	15	

19



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proxxon manufacturer:

Other Similar products are found below :

 PRN28510
 UHZ
 FD 150/E
 24154
 28321
 28856
 PRN20392
 PR23100
 PR23296
 28017
 PR23084
 24140
 24156
 PRN23604
 PRN23000

 TBM 220
 FF 230
 28320
 28720
 28808
 23821
 PRN23090
 28980
 PR23350
 PRN28515
 28752
 28020
 28710
 PRN28472
 28732
 28810

 28854
 23800
 28983
 28812
 28852
 PRN23040
 24152
 28148
 28987
 23820
 2853
 28840
 PRN28820
 PR23822
 MS 4
 28582

 PR23821