



fitted with

work equipment
 connected load
 power consumption
 glare-free
 system of protection
 class of protection
 technology
 usage
 luminaire body
 weight (net)
 mains supply

LED

Energy efficiency category A+
 power supply unit
 220-240V; 50/60Hz
 approx. 26 W
 conical prismatic screen
 IP 20
 I
 switchable
 rocker switch
 aluminium/plastic, ESD-version, black
 approx. 4.3 kg
 connector
 1-polig
 2-polig
 extension range of rise-and-fall pendant 0.3 - 1.3 m

fastening




1-polig






2-polig

illuminance

Distance: 100 cm
 Em: 806 lx
 Emax: 1092 lx
 Emin: 480 lx



luminous intensity



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Lighting Fixtures](#) category:

Click to view products by [Waldmann](#) manufacturer:

Other Similar products are found below :

[XVEC21P](#) [XVEC2B7](#) [113163000-00662717](#) [113472000-00691461](#) [LD6A-3DQB-RYG](#) [LD6A-3DZQB-RYG](#) [LF1B-NA3P-2THWW2-3M](#) [LF1B-NC3P-2THWW2-3M](#) [LF1B-ND3P-2THWW2-3M](#) [E35600](#) [NB-RLAMP01-LED](#) [FLK7LED](#) [LD6A-3WQB-RYG](#) [XVC4B3K](#) [XVBC4M7](#) [2702478](#) [2702479](#) [2702482](#) [2702935](#) [2702934](#) [ZWF-638-24CW](#) [ZAF-486-24CW](#) [BC5000-N-S](#) [BP3200-C-S-24](#) [BP3200-C-F-36](#) [BP3200-C-F-12](#) [BC5000-C-S](#) [2702933](#) [2403122](#) [2403121](#) [2402991](#) [113261000-00641180](#) [113259000-00641174](#) [190007019-00014904](#) [226108019-00610754](#) [4823](#) [4824](#) [4866](#) [4868](#) [11212573001-00514271](#) [113021000-00564565](#) [113473000-00704968](#) [113471000-00704981](#) [NB-RLAMP01](#) [E35500](#) [408001403-00671626](#) [LD6A-3WZQB-RYG](#) [LF1B-NA4P-2THWW2-3M](#) [LF1B-NB3P-2THWW2-3M](#) [LF1D-C2F-2W-330](#)