



894

LED Traffic Light

NEW



LED Traffic Light (2 tier)



LED Traffic Light (3 tier)



Clear lenses ensure signalling effect even in direct sunlight

- High visibility LED Traffic Light in an innovative design
- Clear signalling even in direct sunlight thanks to clear lenses
- Simple mounting thanks to integrated mounting bracket
- Very good sideward visibility

TECHNICAL SPECIFICATIONS:

Dimensions (D x W x H):	2 tier: 136 mm x 85 mm x 311 mm	Life duration up to 50,000 hrs
	3 tier: 136 mm x 85 mm x 396 mm	
Housing:	PC/ABS, grey	
Lens:	PC, transparent	
Fixing:	wall mounting	
Installation position:	vertical/hanging	
Connection:	Screwable connection with wire protection max. 1.5 mm ²	
Cable entry:	Cable diameter max. 13 mm	
Duty cycle:	100 % ED	

ORDER SPECIFICATIONS:

Voltage	24 V =	115 to 230 V ~
Current Consumption	60 mA (red/yellow)	30 mA per tier at 230 V/50 Hz
	120 mA (green)	
red / green	894 160 55	894 160 68
red / yellow / green	894 180 55	894 180 68

ACCESSORIES:

Additional Fixing Bow underneath (see page 145)	975 894 01
---	-------------------

TECHNICAL DIAGRAMS:

see page 299



High visibility LED Traffic Light with integrated siren see page 180


In preparation



2 tier



3 tier





LED Beacon (1 tier)



Innovative design option with the attachment of a second fixing bow (accessory)



The direction of the optical signal can be individually adjusted

- High visibility LED Beacon / Traffic Light in an innovative design
- Colour intensive light effect thanks to LEDs in the same colour as the lenses
- Simple mounting thanks to integrated mounting bracket
- Very good sideward visibility

i TECHNICAL SPECIFICATIONS:	
Dimensions (D x W x H):	1 tier: 136 mm x 85 mm x 226 mm
	2 tier: 136 mm x 85 mm x 311 mm
	3 tier: 136 mm x 85 mm x 396 mm
Housing:	PC/ABS, grey
Lens:	PC, transparent
Fixing:	wall mounting
Installation position:	vertical/hanging
Connection:	Screwable connection with wire protection max. 1.5 mm ²
Cable entry:	Cable diameter max. 13 mm
Duty cycle:	100 % ED

Life duration up to 50,000 hrs

🛒 ORDER SPECIFICATIONS:		
Voltage	24 V =	115 to 230 V ~
Current Consumption	60 mA (red/yellow)	30 mA per tier at 230 V/50 Hz
	120 mA (green)	
red	894 010 55	894 010 68
green	894 020 55	894 020 68
yellow	894 030 55	894 030 68
red / green	894 060 55	894 060 68
red / yellow / green	894 080 55	894 080 68

🏠 ACCESSORIES:	
Additional Fixing Bow underneath	975 894 01

📐 TECHNICAL DIAGRAMS:	
	see page 299



High visibility LED Traffic Light with integrated siren see page 181

In preparation



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Indicators & Alerts](#) category:

Click to view products by [Werma](#) manufacturer:

Other Similar products are found below :

[M2BJ-BH24E](#) [6-4](#) [68S1240-PA](#) [MBA-624](#) [F/BC 40P-DR LF](#) [FDG111PLF](#) [F/NRMB 24 BLACK LF](#) [PF-35N29WQ](#) [PFD-27A35PQ](#) [PL-27A35PSQ](#) [PS-531Q](#) [AB2020B-2-LW1](#) [EBPT-401](#) [PB06SD12AP](#) [PB-1220PEQ](#) [S6109](#) [SC2036ACP](#) [SC616N-2](#) [SC628FW](#) [SC628MPG](#) [SC648D](#) [SCS045MD9DT3S](#) [AB2025B-LW50-R](#) [ESZ-25B-5-250B](#) [F/BC 35-DR LF](#) [FCM12PLF](#) [F/EB20P-DR LF](#) [F/HU110MP24V-IP67B LF](#) [AI-2835-TF-LW150-2-R](#) [AI-4228-TF-LW305-R](#) [FSMD8585JSLF](#) [FSS-26T](#) [F/SU 21-02 LF](#) [F/TCW 05 WITH LABEL LF](#) [F/UCW 03 WITH LABEL LF](#) [F/UCW 06 WITH LABEL LF](#) [PKM22EPPH40S1-B0](#) [PKM35-4A0](#) [PL-35N29WQ](#) [PLD-27A35PQ](#) [PS-552Q](#) [CM-5](#) [M2BJ-BH24E-D](#) [REF-202](#) [LSC628ANR](#) [5-100 PAL-328](#) [03-810.001](#) [RTO-1R07-001](#) [PL-21N31PQ](#) [PF-27A25PSQ](#)