TECHNICAL DATA

Version 10

AT170 Polycloth Laminate Tape

General Description

A gloss polycloth laminate tape coated with an aggressive pressure Sensitive adhesive.

- Strong
- · Easy tear and unwind
- Very high initial tack
- · Good abrasion resistance
- Water resistant finish
- Conformable to awkward shapes
- Non-corrosive adhesive

Technical Details

Typical values

Thickness 0.20mm

Breaking Load 35 N/cm

Elongation 20%

Adhesion

Steel 3.7 N/cm

Self 2.3 N/cm

Moisture Vapour Permeability 25g/m₂/24hrs

RoHS compliant Yes

Service Temperature -50°C to +65°C

Application Temperature +10°C to +45°C

Storage Temperature +12°C to +25°C



NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue Thurmaston Leicester LE4 8PH England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



005026

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Advance Tapes manufacturer:

Other Similar products are found below:

AT7 BLACK 33M X 25MM AT163 SILVER 50M X 50MM AT8 BLACK 33M X 50MM AT541 33M X 12MM AT2000 BLACK 18M X 50MM AT2000 BLACK 18M X 50MM AT525 COPPER 33M X 10MM AT7 BROWN 33M X 25MM AT10 BLACK 33M X 50MM AT2000 WHITE 50M X 50MM AT8 BLUE 33M X 50MM AT8 GREEN 33M X 50MM AT159 BLUE 50M X 25MM AT202 WHITE 50M X 50MM AT2000 YELLOW 18M X 50MM AT2000 BLACK 18M X 100MM AT525 COPPER 33M X 50MM AT159 GREEN 50M X 50MM AT4002 WHITE 55M X 25MM AT9 SILVER 33M X 50MM AT160 BLUE 50M X 50MM AT3400 BLACK 20M X 19MM AT4001 WHITE 55M X 25MM AT30 BLACK 33M X 50MM AT132 WHITE 50M X 50MM AT4004 YELLOW 66M X 25MM AT159 BLACK 50M X 50MM AT160 WHITE 50M X 50MM AT88 RED 33M X 50MM AT85 BLACK 10M X 50MM AT42 ORANGE 33M X 50MM AT7 ASSORTED COLOURS 33M X 19M AT160 YELLOW 50M X 50MM AT8H RED / WHITE 33M X 50MM AT544 33M X 19MM AT544 33M X 19MM AT308 CREAM 25M X 50MM AT7 VIOLET 33M X 25MM AT202 BLACK 50M X 50MM AT30 CLEAR 33M X 50MM AT44 BLACK 33M X 100MM AT85 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT85 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT79 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT79 BLACK 10M X 19MM AT160 REEN 33M X 25MM AT7 RED 33M X 19MM AT27 TRANSPARENT 33M X 25MM