


RoHS  
Compliant



## Specifications:

Material	: Unplasticized Polyvinyl Chloride
Density	: 1,560 kg/m <sup>3</sup>
Hardness Shore D	: 83
Tensile strength at yield	: 45 N/mm <sup>2</sup>
Elongation at yield	: 4%
Impact strength at +23°C	: No Breaking
Impact strength at -40°C	: 60 kJ/m <sup>2</sup>
CHARPY Impact Strength	
at +23°C	: 8.0 kJ/m <sup>2</sup>
at 0°C	: 3.0 kJ/m <sup>2</sup>
at -40°C	: 2.0 kJ/m <sup>2</sup>
Tensile modulus	: 3,600 N/mm <sup>2</sup>
Ball indentation hardness	: 125 N/mm <sup>2</sup>
VICAT softening point method B50	: +82°C
Temperature of use	: -5°C to +65°C
Volume Resistivity	: 1E15 Ω·cm
Dielectric Strength	: 15 kV/mm
Resistance to Tracking	: KC > 600V
Light Resistance	: >6
Stabilization	: Cadmium free, with Lead
Weather Resistance	: Average to Superior

## Standards:

As per UL1565, CSA

## Part Number Table

Description	Part Number
Cable Trunking 50mm × 50mm, 2m Length	0845 0166 010

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)  
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)  
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)  
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)