



- 2.5mm polyurethane insulation
- Conductor is high strength 7-end duplex tinsel for strength and flexibility
- 1 megohm resistor built in each socket
- Colour: black
- Dielectric Strength: Cords withstand 1250 volts DC for at least one minute
- · Standard cords are marked and date coded
- · Both cord ends terminated with 10mm snap socket

Item #	Description
VER-26967	CORD,COILED,3M,10MMSOCKET/10MM SOCKET, BLACK

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 ground cords)

Per Note 6 of Table 1 of EN 61340-5-1 for Working surfaces, storage racks, trolleys and carts "It is allowed, when approved by the ESD co-ordinator, to use surfaces which are 'hard ground' i.e. less than 1 X 10<sup>4</sup> ohms to EPA ground."



Specifications and procedures subject to change without notice.



## Coiled Cords, 3M, 10mm Socket, 10mm Socket

VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL: <u>Service@Vermason.co.uk</u>, INTERNET: <u>Vermason.co.uk</u>

Drawing Number VER-26967 DATE: September 2015

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Vermason manufacturer:

Other Similar products are found below :

<u>072425B</u> <u>229765</u> <u>200535</u> <u>222547</u> <u>222562</u> <u>50424</u> <u>229625</u> <u>242296</u> <u>210320</u> <u>210300</u> <u>35268</u> <u>220522</u> <u>242140</u> <u>47200</u> <u>231250</u> <u>203065</u> <u>237670</u> <u>231288</u> <u>242210</u> <u>242278</u> <u>242291</u> <u>239260</u> <u>222635</u> <u>237195</u> <u>203005</u> <u>241090</u> <u>229100</u> <u>242276</u> <u>230310</u> <u>J6609</u> <u>242271</u> <u>47201</u> <u>242274</u> <u>230480</u> 238711 200520 35594 35595 230660 230500 237675 211045 231275 229775 237200 229755 203015 229630 230260 200515