



General Characteristics

Power	: 7.4V 2200mAh Li-Battery
LCD Size	: 70mm x 52mm
Product Colour	: Orange and Grey
Product Net Weight	: 638.6g
Product Size	: 103mm × 225mm × 59mm
Standard Accessories	: Batteries, Test Lead, Temperature Adaptor, Point Contact Temperature Probe × 2, Power Adaptor
	(UK plug and EU plug), PC Software CD, USB Interface Cable

Specifications:

Basic Functions	Range	Best Accuracy
DC Voltage (V)	60mV/600mV/6V/60V/600V/1000V	±(0.025%+5)
AC Voltage (V)	60mV/600mV/6V/60V/600V/1000V	±(0.3%+30)
DC Current (A)	600µA/6000µA/60mA/600mA/10A	±(0.08%+10)
AC Current (A)	600µA/6000µA/60mA/600mA/10A	±(0.6%+20)
Resistance (Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.05%+2)
Admittance (nS)	60nS	±(2%+10)
Capacitance(F)	6nF/60nF/600nF/6µF/60µF/600µF/6mF/60mF	±(2%+5)
Frequence (Hz)	10Hz to 60MHz	±(0.01%+5)
Temperature (°C)	-40°C to 1000°C	±(1%+30)
Temperature (°F)	-40°F to 1832°F	±(1.5%+50)
Special Functions		
Display Count		60000
Auto Range		\checkmark
Manual Range		\checkmark
True RMS		\checkmark
Bandwidth (Hz)	100kHz	\checkmark
AC + DC		\checkmark
Low Pass Filter	1kHz(-3db)	\checkmark
dBV/dBm		\checkmark
Continuity Buzzer		\checkmark
Diode	Around 3V	\checkmark
Duty Cycle	1% to 99%	\checkmark
Dual Temperature Measurement	T1,T2, T1-T2, T2-T1	\checkmark
Data Hold		\checkmark
Peak Hold		\checkmark
Relative Mode		\checkmark
Data Logging	20000	\checkmark

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com





Trend Capture		\checkmark
MAX/MIN/AVG		\checkmark
Date Time Display		\checkmark
Data Comparsion		\checkmark
Display Type	3.5 Inches 64k Colour TFT LCD (320 × 240)	\checkmark
Backlight Adjustment		\checkmark
USB Interface		\checkmark
Mis-Plug Alarm		\checkmark
Auto Power Off		\checkmark
Re-Chargeable Battery		\checkmark
Input Protection		
Input Impedance for DCV	Around 10MΩ	\checkmark

Part Number Table

Description	Part Number
True RMS Data logging Multimeter	72-3540

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com



X-ON Electronics

Authorized Distributor

Click to view similar products for Tenma manufacturer.

Other Similar products are found below :

<u>2110130UKEU 2110140 2110142 2110144 2110146 2110148 2110150 2110152</u> 2110154 2110156 2110158 2110160 2110162 2110164 2110168 2110170 211040 211041 211042 211045 211046 211047 211050 2110562 2110563