


VAC17KS, North America, V-Lock cord retaining, 2.0 m, Connector C17, SJT 2x18 AWG, white

new



Description

- Power Cord , Protection class II , Pin temperature 70 °C
- with V-Lock interlocking system

Technical Data

Ratings UL/CSA	10A / 125VAC; 50/60Hz	appliance inlet/-outlet	C17 acc. to IEC 60320-1
Dielectric Strength	> 2 kVDC between L-N (1 min/50/60Hz)		UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class II
Allowable Operation Temp.	-25 °C to 60 °C		
IP-Protection	from front side IP 20 acc. to IEC 60529		
Insulation cover	Suitable for appliances with protection class II acc. to IEC 61140		
Terminal	moulded		
Material: Housing	PVC, white		

All Variants

Connector		cable				Plug					Order Number
Type	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Type	Country	Standard	Style	Index	
C17	●	SJT 2x18 AWG	18 AWG	2.0	white	North America	USA	NEMA 1-15	straight	-	6051.2811

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 75 Pcs

Mating Inlets/Plugs shuttered



Category / Description

[Appliance Inlet Overview complete](#)

IEC Appliance Inlet C18, Snap-in Mounting, Solder, Quick-connect, Screw- or PCB Terminal	6015
6061, Mounting: Screw, Appliance Inlet: IEC C14	6061
GSP1, Mounting: Screw, Appliance Inlet, IEC C14, For PCB mounting, IP 40, Quick connect terminals 4.8 x 0.8 mm angled or straight, Suitable for appliances with protection class I or II	GSP1
GSP2, Mounting: Sandwich, Appliance Inlet, IEC C14, For PCB mounting, IP 40, angled to pin axis, Suitable for appliances with protection class I or II	GSP2

[Appliance Inlet further types to 6051.2811](#)

Power Entry Module Overview complete



DC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 1 or 2 pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, Without fuse holder: Suitable for appliances with protection class I or II	DC11
DD11, Mounting: Screw-on mounting, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, With or without protection cover, Fuse holder: 1 or 2 pole, Suitable for appliances with protection class I	DD11
DD21, Mounting: Screw-on mounting Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, additional quick connect 4.8 x 0.8 mm Appliance Inlet: IEC C14, Fuse holder: 1 or 2 pole	DD21
GSF1, Mounting: Fuse holder: optional, 1 or 2 pole, Appliance Inlet: IEC C14, Suitable for appliances with protection class I	GSF1
GSF2, Mounting: Snap-in, Appliance Inlet: IEC C14, Fuse holder: 1 or 2 pole, Solder terminals or quick connect terminals : black, Suitable for appliances with protection class I or II	GSF2
Power Entry Module further types to 6051.2811	...

Power Entry Module with line filter Overview complete



5707, Mounting: Screw, Front-/Rear-Side, Filter: Standard and Medical Version, Fuse holder: 1 or 2 pole, Front Side, 8 A, Appliance Inlet: IEC C14, Suitable for appliances with protection class I or II	5707
5120, Mounting: Screw, Front-/Rear-Side, Filter: Standard and Medical Version, Without fuse holder: 10 A, Themoplast / steel tin-plated Appliance Inlet: IEC C14, Suitable for appliances with protection class I or II	5120
5123, Mounting: Screw, Front-/Rear-Side, Filter: Standard and Medical Version, Without fuse holder: 10 A, Themoplast / steel tin-plated Appliance Inlet: IEC C14, Suitable for appliances with protection class I or II	5123
Power Entry Module with line filter further types to 6051.2811	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schurter](#) manufacturer:

Other Similar products are found below :

[4302.0101](#) [0034.3429](#) [0034.7115](#) [0040.1101](#) [0001.1007.PT](#) [0034.2515](#) [0034.3406](#) [7030.3280](#) [FMAC-0932-1610](#) [FMAC-0934-3610](#) [FMAD-0931-0810](#) [FMBD-B92B-2512](#) [FMBD-B92C-6412](#) [FMW-65-0005](#) [1241.2506](#) [1301.9211](#) [9632.5100](#) [FMAC-091C-1610](#) [FMAD-0932-2510](#) [FMBC-0994-1000](#) [3-101-015](#) [TA35-C324L080C0](#) [4304.5043](#) [4420.0361](#) [4740.3000](#) [5500.2065](#) [5500.2069](#) [5500.2655.01](#) [4303.1061](#) [4400.0341](#) [4430.2907](#) [DKIH-3358-50C8](#) [DKIP-0333-5001](#) [0865.9851](#) [091132B](#) [5120.1006.0.21](#) [CD24.4101.151](#) [3404.0043.11](#) [6136.0137.0210](#) [FMAC-0934-5010](#) [FMBC-A91U-0710](#) [EC12.1101.001](#) [FMAC-0932-2510](#) [FMAC-3RYB-2010](#) [7010714013](#) [1068.1012.1110001](#) [8020.5071](#) [TA35-CFTBLJ04C0](#) [1241.2903.002](#) [1241.2855](#)