Tip Extraction Units

FT 12

Small, portable, compressed air driven fume extraction unit



Attributes

- > Up to 2 FE soldering irons can be connected
- > Maintenance-free compressed air converter
- > Portable unit for stand alone applications
- > for industrial long terme use

The fume extraction unit FT 12 requires clean and oil-free compressed air. The vacuum is generated by a maintenance-free compressed air converter. The contaminated air is purified by a pre-filter and main filter system. A compressed air cleaning filter removes additional odours caused by the compressed air. This highly efficient filter system makes the FT 12 a genuine air recovery system.

The FE (Fume Extraction) soldering irons are connected directly to the unit – additional leads are not required.



Technical Data	
Maximum capacity	2 FE soldering irons
Noise level	< 37 db (A) at 1 m distance
Maximum vacuum	20.000 Pa
Operating pressure	3,5-7 bar
Air consumption	27 l/min
Height	200 mm
Diameter	120 mm
Weight	1,7 kg

Scope of supply


- > FT 12 Fume extraction unit
- > Compressed air cleaning filter
- > Compact filter
- consists of: Particle filter H13, Wide band gas filter (50 % active carbon, 50 % Chemisorb) > Fine dust filter F7

Order No.

112-0000-ESD

Spare parts & Accessories

Order No.
300-2000
300-2001
300-2002



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Weller manufacturer:

Other Similar products are found below :

XPE700
ST-4
ST-3
0054005799
0058744845
0054465399
6120
7324
PL138
PTH6
HE35
DXV80
NTD
T0051387699
T0051607599

T0052916199
T0053418699
T0053427699
T0053434699
T0053638699
T0054486299
T0058732869
PSI5
HEW60P
LT4X
CT6E7

51314700
WHP80
WTA1
WTA4
DS227
DX120
RT6MS
RTW3MS
SP40NUS
T0051302699
T0051390699
T0052704299

T0053429699
T0053438699
T0053657199
T0054480299
T0058744730
TC208
CT5AA8
WPT15
WLSK200

WEL.51361699
WEL.51361699
Setup
Set