

Data Sheet

SUCOFLEX_Stock Assembly

Description

The SUCOFLEX 126_EA high end cable assemblies are designed to provide optimal performance up to 18 GHz where stringent electrical requirements – in particular stability and low loss, are important. Protected by an A-ruggedisation, the SUCOFLEX 104PE becomes a flexible and robust test and measurement cable!

Product description SF126EA/SMAM/SMAM/1000mm
Item number 85072827



Product Configuration

Cable type	SUCOFLEX_126_E
A-Ruggedisation	Steel wire spring, steel braid, TPU jacket blue
Length of assembly	1'000 mm
Connector A	SMA straight male
Connector B	SMA straight male

Technical Data

Mechanical Data

Diameter:	10.3 mm
Min. bending radius static	30 mm
Min. bending radius repeated	50 mm
Recommended mating torque (*)	0.8...1.1 Nm
Weight	166 g

Environmental Data

Operating temperature	- 40°C to + 85°C
Storage temperature	- 40°C to + 85°C
RoHS, REACH	Compliant

Electrical Data

Impedance	50 Ω
Operating frequency	up to 18 GHz
Velocity of propagation	77 %
Capacitance	87 pF / m
Time delay	4.3 ns / m

Return Loss	min. 19.0 dB	(up to 18 GHz)
Insertion loss (assembly)	max. 1.43 dB	(18 GHz, 25°C)
Power handling	min. 144 W	(18 GHz, sea level, 25°C)
Insertion loss stability vs. bending (**)	+/- 0.2 dB	(up to 18 GHz)
Phase stability vs. bending (**)	< 0.9°	(el/GHz)

General Information

(*) H+S torque wrench H+S description: 74_Z-0-0-21 // material/item number: 22543130
 (**) Stability test 360°, diameter 55 mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[3402.17.A](#) [31 MMBX-SMA-50-1/111 NE](#) [74Z-0-23-17](#) [65 SMA-50-0-1/111 NE](#) [32 MMBX-50-0-6 / 111 NE](#) [Mini141 K-16](#) [7404.17.0003](#)
[33_N-SMA-50-51/1--_UE](#) [76_Z-0-2-1](#) [Minibend L-13](#) [Microbend MTR-11](#) [16_N-50-3-103/133_NE](#) [Microbend R-4.5](#) [74_Z-0-0-53](#)
[85_SMC-50-0-1/133_NE](#) [31_PC35-50-0-2/199_NE](#) [65_BNC-50-0-2/133_NE](#) [1399.17.0125](#) [76_Z-0-4-1](#) [80346275](#) [11_C-50-7-6/133_NE](#)
[6620_SMA-50-2/199_NE](#) [Minibend R-5.5](#) [11_SMB-50-2-41/111_NE](#) [Mini141 K-8](#) [74_Z-0-0-246](#) [22_BNC-50-0-5/133_NE](#) [6500_N-50-](#)
[1/199_NE](#) [6560.17.AA](#) [3401.17.0033](#) [11_N-50-2-1/133_NE](#) [3401.00.0022](#) [74_Z-0-0-142](#) [11_QLA-01-2-8/122_NE](#) [34_BNC-50-0-6/100_NE](#)
[74_Z-0-0-59](#) [Minibend R-6.5](#) [21_N-75-4-8/133_NE](#) [24_BNC-75-2-1/133_NE](#) [24_H4-50-3-1/133_NE](#) [Minibend-14](#) [31_SHV-50-0-1/133_NE](#)
[23_SK-50-0-52/199_NE](#) [74_Z-0-0-214](#) [23_BNC-50-0-2/133_NE](#) [74_Z-0-0-60](#) [33_SK-PC24-50-1/199_NE](#) [24_N-50-7-8/133_NE](#) [74_Z-0-0-](#)
[157](#) [6810_N-50-1/1--_NE](#)