

PFA61

- 67GHz SOLUTIONS
- LOW LOSS/VSWR
- DOUBLE SHIELDED
- TIGHT MIN BEND
- LIGHT WEIGHT



TESTeLINK RF Cables



Professional High Frequency RF Test Cables.

Connector Choices Include;
1.85mm(V), 2.4mm, 2.92mm(K), & 3.5mm.

Key Features;

- Hi-Frequency Point to Point Cable
- Light Weight with Low Min Bend
- Low Loss <2.07db/ft @ 67GHz
- Low VSWR < 1.45:1 (Typical < 1.30:1)
- RF Leakage >-100dB to 18GHz
- Temp. Rated from -50°C to 125°C

Configuration Chart

PFA61-B1B1-S24

PFA61-YYZZ-YYY

YYZZ = Connector Options

1.85mm Male (67GHz) = B1
1.85mm Female (67GHz) = BF
2.4mm Male (50GHz) = C1
2.4mm Female (50GHz) = CF
2.92mm Male (40GHz) = D1
2.92mm Female (40GHz) = DF
3.5mm Male (32GHz) = E1
3.5mm Female (32GHz) = EF

YYY = Length Options

FYY = Length in Feet(F06 = 6ft)
SYY = Length in Inches(S18 = 18")
YMY = Length in Meters(2M5 = 2.5m)
CYY = Length in Centimeters(C30 = 30cm)

TESTeLINK RF Cables

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CONDUCTRF](#) manufacturer:

Other Similar products are found below :

[SF18G-N1S1-F05](#) [VNA18-N1N1-S24](#) [VNA40-DNFD1-S24](#) [SF27G-E1EF-1M0](#) [SW50G-C1CF-1M0](#) [TSA74-N1S1-1M0](#) [PFA61-D1D1-1M0](#)
[SF27G-EFEF-1M0](#) [PFA61-C1C1-1M0](#) [SF07G-N1D1-F05](#) [SW50G-CFCF-1M0](#) [VNA18-N1NF-S24](#) [SF18G-N1N2-1M0](#) [SF09G-N1N1-F05](#)
[TEA90-N1S1-1M0](#) [SF09G-N1NF-F05](#) [TEA90-N1N1-1M0](#) [SF18G-N1NF-1M0](#) [SF18G-N1N1-1M0](#)