

TSA74

- LOW LOSS
- AMPLITUDE STABLE
- PHASE STABLE
- TRIPLE SHIELDED
- HIGH POWER HANDLING



TESTeCON Low Loss



Low Cost Professional RF Test Cables

Designed to Support Major RF Test Lab's

Versatile Solution;

- Phase Stable Testing ± 4 Deg to 18GHz
- Amplitude stable to ± 0.2 dB to 18GHz
- Max Power 170W @ 18GHz
- Flex Life over 10,000 Cycles
- Cable Loss < 0.330 dB/ft @ 18GHz
- VSWR $< 1.35:1$ (Typical $< 1.20:1$)

Configuration Chart

TSA74-S1S1-S18

TSA74-YYZZ-YYY

YYZZ = 18GHz Connector Options

SMA Male = S1
SMA Female = SF
Type-N Male = N1
Type-N Female = NF
TNC Male = T1
TNC Female = TF
3.5mm Male = E1
3.5mm Female = EF

YYY = Length Options

FYY = Length in Feet (F06 = 6ft)
SYY = Length in Inches (S18 = 18")
YMY = Length in Meters (2M5 = 2.5m)
CYY = Length in Centimeters (C30 = 30cm)

TESTeCON RF Cables

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CONDUCTRF](#) manufacturer:

Other Similar products are found below :

[SF18G-N1S1-F05](#) [VNA18-N1N1-S24](#) [VNA40-DNFD1-S24](#) [SF27G-E1EF-1M0](#) [SW50G-C1CF-1M0](#) [TSA74-N1S1-1M0](#) [PFA61-D1D1-1M0](#)
[SF27G-EFEF-1M0](#) [PFA61-C1C1-1M0](#) [SF07G-N1D1-F05](#) [SW50G-CFCF-1M0](#) [VNA18-N1NF-S24](#) [SF18G-N1N2-1M0](#) [SF09G-N1N1-F05](#)
[TEA90-N1S1-1M0](#) [SF09G-N1NF-F05](#) [TEA90-N1N1-1M0](#) [SF18G-N1NF-1M0](#) [SF18G-N1N1-1M0](#)