

Mike 3A

IP67 GPS Magnetic Mount Patch Antenna



Key Features

- 28dB LNA gain
- **IP67** protection •
- Dual mount
- Various cable lengths available
- · Ground plane independent
- RoHS compliant

General Description

Siretta's range of latest generation GPS patch antennas offer excellent performance characteristics and flexibility when installing via its magnetic mount. The Mike 3A is also supplied with an adhesive pad for non IP67 applications.

The Mike 3A family are embedded with the latest generation, two stage, preamplifier circuit offering 28dB LNA gain. Capable at operating within 3-5V. Its low current draw of just 10mA at 3V heps keep the operating voltage to a minimum making it suitable for applications where power saving is important.

Measuring just 47mm x 35mm x 17mm ± 1mm, the Mike 3A can be supplied with a variety of connectors or cable lengths.

Additional Considerations

- Improves signal to noise ratio for mobile applications
- Extended mounting choose from magnetic or adhesive pad ٠
- Ideal for routing around vehicle interior
- · Can be mounted on wide ranging surfaces
- · Meets all EU compliance criteria for electronic goods

Rev 1 1

A member of the Olancha Group Ltd Registered in England No. 08405712 VAT Registration No. GB163 04 0349

Siretta Ltd Basingstoke Road Spencers Wood Reading Berkshire RG7 1PW

+44(0)118 976 9014 +44(0)118 976 9020 email sales@siretta.co.uk www.siretta.co.uk

sales

fax

web



Mike 3A IP67 GPS Magnetic Mount Patch Antenna

Key Specifications - Electrical

Temperature range:	-40 to +85°C
Impedance:	50 ohm
Gain:	28dB
VSWR:	2.0 max
Voltage / supply cu and example:	rrent 3 - 5V DC / 8023mA (3V @ 10mA)
Centre	1.575.42MHz ± 1.023MHz
frequency:	(covered with random and measured on ground plane)
Polarization:	RHCP
Bandwidth:	10Mhz (10dB return loss)
Amplifier:	2 stage LNA with SAW filter for out of band attenuation
Noise figure:	1.4dB typical
Axial ratio:	1.0dB typical

Key Specifications - Mechanical

Dimensions:	47mm x 35mm x 17mm ± 1mm (without cable)
Cable:	RG174 (for lengths, please refer to options table below)
Connector:	SMAm, SMBm plug, MCXm, MMCXm
IP rating:	IP67 (magnetic mount only)
Mounting method:	Magnetic or adhesive (3M pad supplied loose in bag)

Ordering Details	
Part Number	Description
MIKE3A/2.5M/SMAM/S/S/17	GPS, IP67 Mag Mount GPS Antenna, 2.5M Cable, SMAM Male Connector.
MIKE3A/3M/MCXM/S/S/17	Magnetic/Adhesive Mount GPS Antenna, 3m Cable, SMA Male Connector
MIKE3A/3M/MMCXM/S/S/17	Magnetic/Adhesive Mount GPS Antenna, 3m Cable, MMCX Male Connector

VAT Registration No. GB163 04 0349

Berkshire RG7 1PW

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for SIRETTA manufacturer:

Other Similar products are found below :

ALPHA4A/5M/SMAM/S/S/26_DELTA5A/X/SMAM/S/S/17_OSCAR17/X/TNC/S/S/19_DELTA5A/X/BNCM/S/S/17_SNYPER-LTE-SPECTRUM_ASMA2000F058L13_ASMA2000C058L13_TANGO14/5M/LL/SMAM/S/S/24_TANGO1/1M/FMEF/S/S/4_ASME500F058L13 TANGO3/0.5M/SMAM/S/S/31_TANGO40/X/NTYPEF/S/S/32_QUARTZ-W22-LTE(EU)+ACC_ASMA500B174L13_31557 ECH040/0.1M/UFL/S/S/32_MIKE1A/5M/FMEF/S/S/20_QUARTZ-W22-UMTS(EU)+ACC_TANGO11A/2.5M/SMAM/S/S/19 ASMA500F058L13_ZETA-N-UMTS_ECH011/0.2M/IPEX/S/S/12_ASMA300E174L13_ASMA1000F058L13_DELTA19/X/SMAM/S/S/35 ASMA2000E058L13_ASMZG300F058L13_MIKE3A/5M/SMAM/S/S/17_TANGO15/3M/SMAM/SMAM/S/S/24 TANGO20/3M/SMAM/S/S/26_ASMZG500A058L13_ASMZG1500F058L13_ALPHA1A/2.5M/SMAM/S/S/11_ OSCAR40/10M/LL/SMAM/S/S/33_TANGO11A/5M/LL/SMAM/S/S/19_TANGO29/1M/SMAM/RP/S/35_ASME2000F058L13 ASMK015X174S11_LC300-N2-GPRS_DELTA6A/X/SMAM/S/S/11_MIKE1A/2.5M/FMEF/S/S/20_ASMZG1000F058L13_ OSCAR41/X/NTYPEF/S/S/29_TANGO22/3M/SMAM/SMAM/SMAM/26_OSCAR420/0.4M/NTYPEF/S/S/19_ASMK010X174S11_ZETA-N2-GPRS_ADAPT/SMAF/SMAM/RP_OSCAR18/X/NF/S/S/22_TANGO14/3M/SMAM/S/S/24