

# EAO – Your Expert Partner for Human Machine Interfaces

## 82-5151.2000.B001 Pushbutton 19mm stainless-steel

### 82-5151.2000.B001 Pushbutton 19mm stainless-steel



Configuration number : 82-10-001672

#### Mounting

Mounting cut-out Ø 19 mm  
Design flush

#### Front

Front dimension Ø 22 mm  
Front shape round  
Front ring shape flush  
Front bezel material Stainless steel

#### Other Attributes

Weight 0.018 kg

#### Operating-/Indication part

Lens optics opaque  
Lens material Stainless steel  
Lens colour Stainless steel  
Lens profile flat ISO 71 On/Off symbol  
Lens illumination non-illuminative

#### IP-Rating

Front protection IP 65, IP 67, IK10

#### Connection Method

Terminal Solder/ Plug-in 2.8 x 0.5 mm

#### Actuator

Switching action Maintained (latching)

#### Switching element

Switching current 5 A  
Contact material Silver  
Contacts 1 C  
Switching system Snap-action switching element  
Switching voltage 250 V AC  
Typical switch ratings 0.7A@24VDC, 0.5A@220VAC


#### Function

Pushbutton


# EAO – Your Expert Partner for Human Machine Interfaces

82-5151.2000.B001 Pushbutton 19mm stainless-steel


## Dimensions




## Mounting cut-outs



## Wiring diagram



## Component layout



## Legend

Switching action: C = Maintained

Contacts: C = Changeover

**Pushbutton**
**Switching system**

Snap-action changeover contact normally closed / normally open.  
Switching function momentary or maintain.

**Material**
**Housing**

Stainless-steel polished or brushed  
Brass nickel-plated or galvanically gold-plated

**Terminal housing**

Polyamide 66 (PA66)

**Contact material**

Silver alloy

**Mechanical characteristics**
**Mounting cut-out**

Ø19 mm +0.3/+0.1 mm

**Terminals**

Soldering terminals 2.8 x 0.5 mm

**Tightening torque**

5 Nm min. – 12 Nm max. for fixing nut

**Actuating force**

3 ... 6 N

**Actuating travel**

Pushbutton momentary 2.5 mm  
Pushbutton maintain 3 mm

**Mechanical lifetime**

Pushbutton momentary 1 Mio. cycles of operation  
Pushbutton maintain 500 000 cycles of operation

**Resistance to heat of soldering**

Hand-soldering 260 °C, 3 sek.

**Electrical characteristics**
**Rated Operational Voltage  $U_o$** 

250 VAC

**Rated Insulation Voltage  $U_i$** 

250 V

**Illumination**

LED red, green, blue, yellow, orange and white  
LED and series resistor with polarity protection are built in.

Voltage	Current
3.5 VDC	15 mA
6 VAC/DC	15 mA
12 VAC/DC	14 mA
24 VAC/DC	10 mA
110 VAC	2 mA
230 VAC	1.3 mA

**Contact resistance**

<50 mΩ

**Electrical life**

100 000 cycles of operation

**Switch rating IEC 60947-5-1**

Switch rating AC cosφ 0.3 service categorie AC-15

Voltage	Current
24 VAC	1 A
110 VAC	1 A
220 VAC	0.5 A

Switch rating DC service categorie DC-13

Voltage	Current
24 VDC	0.7 A
110 VDC	0.2 A
220 VDC	0.1 A

**Switch rating UL 508**

Switch rating AC cosφ 0.75 ... 0.8)

Voltage	Current
120 VAC	5 A
240 VAC	3 A

Switch rating DC

Voltage	Current
24 VDC	1 A

**Conventional free air thermal current  $I_{th}$** 

5 A

The maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

**Electrical strength**

2500 VAC, 50 Hz 1 min. between life terminals and ground  
1000 VAC, 50 Hz 1 min. between life terminals

**Isolation resistance**

500 VDC at min. 10 MΩ according to IEC 60512-2

**Environmental conditions**
**Storage temperature**

-40 °C ... +80 °C

**Operating temperature**

-30 °C ... +70 °C

**Front protection**

IP 65 and IP 67, as per IEC 60529

**Impact resistance**

IK 09, as per IEC 62262

**Shock resistance**

max. 500 m/s<sup>2</sup> according to IEC 60068-2-27

**Degree of pollution**

2, as per EN IEC 60947-1

## Pushbutton

### **Vibration resistance**

10 ... 55 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

### **Climate resistance**

Damp heat, 21 days according to IEC 60512-11

Saline mist, 96 hours according to IEC 60512-11

### **Approvals**

#### **Approbations**

CB

UL

CCC

#### **Declaration of conformity**

CE

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [EAO manufacturer](#):*

Other Similar products are found below :

[01-151.022](#) [01-951.6](#) [02-072.001](#) [61-0029.0](#) [61-221.50D](#) [61-2601.0/D](#) [61-2607.0/D](#) [61-2701.0/D](#) [61-8520.12](#) [61-8640.11](#) [704.012.618](#)  
[704.032.218](#) [704.062.5](#) [704.122.018](#) [704-6012](#) [704.902.3](#) [704-9051](#) [704.918.5](#) [704.942.5](#) [70-911.0](#) [EUS-704.000.7](#) [82-4151.2144](#) [82-](#)  
[4153.1000](#) [84-8001.5640](#) [84-8510.0040](#) [95-900.005](#) [14-136.025K](#) [200-4001-00](#) [22-212.011](#) [92-440.000](#) [95-900.009](#) [96-932.5](#) [22-225.011](#)  
[22-901.2](#) [31-426.036](#) [45-2134.4F10.000](#) [45-2231.22E0.000](#) [45-280X.1C90.003](#) [45-2C37.1920.000](#) [45-2T00.10E0.000](#) [51-401.036K](#) [31-953.3](#)  
[31-955.4](#) [41-461.036](#) [41-908.5/5](#) [45-1131.3150.000.101](#) [45-2231.31H0.000](#) [45-2234.4FH0.000](#) [45-50J.1400](#) [51-155.025D](#)