




Produktname | *Product name*: T200F
 Artikelnummer | *Part Number*: 1600-0138
 Anfragenummer | *Inquiry Number*: AN201525
 Ersteller / Datum | *Creator / Date*: LHE / 09.02.2016

Version	Change	Date	Name
V2	name changed	27.03.2016	LHE
V1	technical data	10.08.2016	LHE
V0	---	09.02.2016	LHE

Lampe / lamp



Allowable deviation / general tolerances DIN ISO 2768-c

Technische Daten T200F / technical data T200F:



LED-Leuchtmittel:	3W LED (Fokussierbar)	Main LED illuminant:	3W LED (Focus able)
Schalterfunktion:	1. 100% Modus	Switch function:	1. 100% mode
	2. Eco Modus		2. Eco mode
	3. Aus		3. Off
Leuchtdauer:	Eco Modus: ca. 12 Stunden	Run time:	Eco mode: approx. 12 hours
	100% Modus: ca. 3 Stunden		100% mode: approx. 3 hours
Lichtstrom: [Lumen]	100% Modus: 200lm	Luminous flux (light output): [Lumen]	100% mode: 200lm
	Eco Modus: 80lm		Eco mode: 80lm
Maximale Lichtstärke: [Candela]	100% Modus: 7650cd	Peak beam / luminous intensity: [Candela]	100% mode: 7650cd
	Eco Modus: 2520cd		Eco mode: 2520cd
Maximale Beleuchtungsstärke: [Lux]	100% Modus: 7650lx (Abstand: 1m)	Peak beam illuminance: [Lux]	100% mode: 7650lx (Distance: 1m)
	Eco Modus: 2520lx (Abstand: 1m)		Eco mode: 2520lx (Distance: 1m)
Leuchtweite:	100% Modus: 175m	Beam distance:	100% mode: 175m
	Eco Modus: 100m		Eco mode: 100m
Benötigte Zellen:	3x AAA Micro 1.5V Batterien (Alkaline; LR03/AM4/MN2400)	Battery:	3x AAA Micro 1.5V batteries (Alkaline; LR03/AM4/MN2400)
Schutzart des Gehäuses:	IP54	Degree of protection by the enclosure:	IP54
Gehäusematerial:	Aluminium	Housing material:	Aluminium
Betriebstemperatur:	-10°C...25°C	Operating temperature:	-10°C...25°C
Lagertemperatur:	-10°C...50°C (Nur Alkaline Batterien)	Storage temperature:	-10°C...50°C (Alkaline batteries only)
	-20°C...70°C (Nur Lampe)		-20°C...70°C (Torch only)
Empfohlene Lagerbedingungen: (Nur Alkaline Batterien)	Temperatur: 5..25°C Luftfeuchtigkeit: 45..75%	Recommended storage conditions: (Alkaline batteries only)	Temperature: 5...25°C Rel. humidity: 45...75 %
Approbationen:	CE	Approvals:	CE
Gewicht:	112g nur die Lampe 146g mit 3x Batterien (wie oben beschrieben)	Weight:	112g only the torch 146g with 3x batteries (as described above)
Lieferumfang:	- 3x Batterien (wie oben beschrieben) - Tragegurt - Batteriekartusche	Shipment:	- 3x batteries (as described above) - Lanyard - Battery cartridge
Verpackung:	Farbige Faltschachtel	Package:	Coloured folding box

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ansmann](#) manufacturer:

Other Similar products are found below :

[5020012](#) [1001-0020-UK](#) [1000-0003](#) [1001-0014-UK](#) [1600-0063](#) [1520-0004](#) [5013253](#) [5819083](#) [1600-0145](#) [5030921](#) [5030892](#) [1501-0004-1](#)
[5707173](#) [1600-0153](#) [1600-0199](#) [5030852](#) [5013233](#) [1600-0138](#) [10950964/01](#) [5024063-UK](#) [5030792](#) [ENERGY CHECK LCD](#) [5000023](#)
[5013243](#) [5030902](#) [5030922](#) [1250-0014](#) [BCA120-350](#) [1600-0159](#) [5030912](#) [5016243](#) [1900-0019](#) [5030802](#) [2310-3001](#) [5015643](#) [5035352](#)
[5030982](#) [5311113 / APS 1000](#) [5035391](#) [5015663](#) [2310-3007](#) [5015293](#) [5035371-01](#) [5030992](#) [5030772](#) [5035222](#) [5001183](#) [2312-3003](#)
[5035342](#) [5015313](#)