Product Specifications





MP-5ES-5 | 6-569550-2

Modular Plug Kit, category 5E, 8P/8C, shielded, 4.8 – 5.6 mm max cable jack OD, 8-position, 500/bag

Body Features

Conductor Type Solid | Stranded Shield Material Copper alloy Shield Plating Material Nickel

Configuration Features

Number of Positions 8
Keyed No

Contact Features

Contact Base Material Phosphor bronze

Contact Mating Area Plating Material Gold

Contact Mating Area Plating Thickness 50.00 µin | 1.27 µm

Number of Contacts Loaded 8

Dimensions

Cable Jacket Outside Diameter Range 0.190-0.220 in | 4.8-5.6 mm Conductor Outside Diameter 0.034-0.039 in | 0.86-0.99 mm

Conductor Wire Size 26–23 AWG

Housing Features

Housing Material Glass filled polycarbonate

Industry Standards

UL Flammability Rating UL 1863

Packaging Features

Packaging Quantity 500

Product Availability

Region Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Features

Cable Type Round, shielded
Performance Category Category 5e
Connector Style Plug

Product Specifications



MP-5ES-5 | 6-569550-2

Jack TypeRJ45Latch StyleStandardProduct TypeConnectorShieldedYes

Termination Features

Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Commscope manufacturer:

Other Similar products are found below:

619916-000 1059313 1147587 1155379 1193746-ZZ 1228435 1235477 1237845 1238918 1242458-ZZ 1250727 6050315011 804370-000 CS2130-000 CU5583-000 165592-000 190356-000 1918810-1 232268-000 5267358502 CK0475-000 CK4385-000 CK9479-000 552769-2 CW7879-001 1342754 1-1116734-0 1-1499520-5 1-1657014-7 1-1671215-1 1-1933285-0 1-1933400-0 1-1933582-3 1-1933686-1 1-553292-1 1-556127-5 1-556148-0 1-6278897-0 1-6278897-5 1-6374658-1 1-6693951-0 1278118-5 1278323-2 1278346-2 1278755-4 1375014-2 1375158-1 1375161-1 1375257-1 1435808-1