TECHNICAL DATA

Version 6

AT4001 Class B 130°C Glass Cloth Tape

General Description

A single-sided woven glass cloth tape with a thermosetting solvent based rubber-resin adhesive.

- Rubber thermosetting adhesive
- High temperature resistance.
- High mechanical strength

Specification

Recognised by UL (test method UL.510) and conforms to EN 60454-3-8 Type 1*.

Technical Details

Typical Values

Thickness 0.18mm

Breaking Load 280 N/cm

Elongation 5%

Adhesion to steel 4.0 N/cm

RoHS Compliant Yes

Breakdown Voltage 2.5kV

Service Temperature 0°C to +130°C

Application Temperature +10°C to +40°C



NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

^{*}Standard charge for certificate: £25.00.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Advance Tapes manufacturer:

Other Similar products are found below:

AT7 BLACK 33M X 25MM AT163 SILVER 50M X 50MM AT8 BLACK 33M X 50MM AT541 33M X 12MM AT2000 BLACK 18M X 50MM AT2000 BLACK 18M X 50MM AT525 COPPER 33M X 10MM AT7 BROWN 33M X 25MM AT10 BLACK 33M X 50MM AT2000 WHITE 50M X 50MM AT8 BLUE 33M X 50MM AT8 GREEN 33M X 50MM AT159 BLUE 50M X 25MM AT202 WHITE 50M X 50MM AT2000 YELLOW 18M X 50MM AT2000 BLACK 18M X 100MM AT525 COPPER 33M X 50MM AT159 GREEN 50M X 50MM AT4002 WHITE 55M X 25MM AT9 SILVER 33M X 50MM AT160 BLUE 50M X 50MM AT3400 BLACK 20M X 19MM AT4001 WHITE 55M X 25MM AT30 BLACK 33M X 50MM AT132 WHITE 50M X 50MM AT4004 YELLOW 66M X 25MM AT159 BLACK 50M X 50MM AT160 WHITE 50M X 50MM AT88 RED 33M X 50MM AT85 BLACK 10M X 50MM AT42 ORANGE 33M X 50MM AT7 ASSORTED COLOURS 33M X 19M AT160 YELLOW 50M X 50MM AT8H RED / WHITE 33M X 50MM AT544 33M X 19MM AT544 33M X 19MM AT308 CREAM 25M X 50MM AT7 VIOLET 33M X 25MM AT202 BLACK 50M X 50MM AT30 CLEAR 33M X 50MM AT44 BLACK 33M X 100MM AT85 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT85 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT79 BLACK 10M X 19MM AT159 WHITE 50M X 25MM AT175 GREEN 50M X 50MM AT159 YELLOW 50M X 50MM AT79 BLACK 10M X 19MM AT160 REEN 33M X 25MM AT7 RED 33M X 19MM AT27 TRANSPARENT 33M X 25MM