



HY433/12 NYH

12 pole natural polyamide PA6.6 pillar terminal block 10mm pitch 32a 450v



SPECIFICATION

| | |
|---------------------------------------|--------------------------|
| Number of Poles | 12 |
| Terminal Material | OT58 nickel plated |
| Body Material | Polyamide PA6.6 |
| Colour | Natural |
| Glow Wire Resistance Test Temp | GWIT775°C (EN60695-2-13) |
| Max Conductor Size (Sq mm) | 4 |
| Max Current (A) | 32 |
| Max Voltage (V) | 450 |
| Working Temperature | 110 |
| Pitch (mm) | 10 |
| Height (mm) | 19.5 |
| Width (mm) | 20.2 |
| Length (mm) | 116.7 |
| Diameter (mm) | 3.2 |
| Flammability Rating | UL94V2 and GWIT775°C |
| Terminal Screw Material | White zinc plated steel |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hylec manufacturer](#):

Other Similar products are found below :

[THB.387.D2A](#) [LN167001](#) [THB.391.A3A](#) [50.625 PA/3X7](#) [THB.406.A1G](#) [THB.387.A4A.R](#) [K150-1050-00](#) [K151-1025-00](#) [K151-1063-00](#)
[50.625 PA/R7035](#) [50.216 MPOT-F](#) [K150-1032-00](#) [THB.382.A1A-KIT](#) [K341-1020-00](#) [50.616M/EMVDL-F](#) [GHG9601955R0004](#) [K160-1016-00](#) [K160-1050-00](#) [K150-1040-00](#) [HYKS-07612PP](#) [THB110A6B-F](#) [K151-1032-00](#) [THB.380.3ASSY](#) [THB.384.B1A](#) [50.216 ES](#)
[THK.404.X2A00-F](#) [TTK25BK-SD-F](#) [THB.405.B2A](#) [THB.405.A2B](#) [K160-1063-00](#) [THB.390.C1A](#) [THB.405.A2A](#) [1026010004-F](#) [50.625 ES](#)
[THB.405.A2G](#) [THA.209.A1A](#) [THB.387.D4A](#) [THB.387.C5A](#) [K160-1025-00](#) [50.625 M/EMVDL-F](#) [K160-1040-00](#) [THC.027.A1A](#)
[GHG9601955R0022](#) [THB.387.D5A](#) [K150-1020-00](#) [6000337BC](#) [THB.384.A1A](#) [THK.209.44](#) [5665/221](#) [THB.387.A4A](#)