## INTERCONNECTION

PCB TERMINAL BLOCKS

INTER-CONNECTION

FUSES & FUSE-HOLDERS

LEDS & INDICATORS

MINIATURE **SWITCHES** 

LIMIT & SAFETY SWITCHES

CONTROL PRODUCTS

INTERFACE MODULES & SUPPORTS

RELAY BASES

DIN RAIL **ENCLOSURES** 

**BATTERIES** 

SOLAR PANELS

TRANS-**FORMERS** 

### **Screw to Screwless Terminal strips**


- · Moulded in UL94-V2 self extinguishing PA66
- · Fast connection of two or four solid conductors
- · Screw to screw earth terminal
- · Raised screws for easier insertion of conductors
- 12-poles, 2-poles plus earth, 3-poles plus earth or 4-poles plus earth
- 12-pole types can be pre-cut to specified number of poles
- All earth types marked with symbols for Live, Earth and Neutral

- · CE 72/73 and 93/68
- · Compliant with EN60598 4.7 and 11.2 (EN60598/1 for CTS4P series)
- All tests from EN60998-1, EN60998-2-1 and EN60998-2-2
- · ♠, **( €**& **€** approved

SPECIFICATION		
Ratings (max)		24A/450V
Working temperature		110°C
Moulding		UL94-V0 self extinguishing PA66
Earth insert		Nickel-plated brass
Push-in terminal	Insert	Steel
	Clamping spring	Stainless Steel
Fixing pitch		10mm




		CONNECT	TING CAPACITY	CONDUCT	OR SECTION (MIN)				EARTH INSERT	FIXING HOLE
TYPE NO.	POLES	SCREW	FAST (RIGID)	SCREW	FAST (RIGID)	LENGTH	WIDTH	HEIGHT	DIAMETER	DIAMETER
CTS2P/12	12	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	119mm	19mm	20mm	-	2.8mm
CTS2P/3E	3 (2+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	27mm	27.5mm	20mm	4.1mm	2.8mm
CTS2P/3ES	3 (2+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm <sup>2</sup>	27mm	27.5mm	20mm	4.1mm	drill 3.2mm
CTS2P/4E	4 (3+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	37mm	27.5mm	20mm	4.1mm	2.8mm
CTS2P/4ES	4 (3+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	37mm	27.5mm	20mm	4.1mm	drill 3.2mm
CTS2P/5E	5 (4+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	47mm	27.5mm	20mm	4.1mm	2.8mm
CTS2P/5ES	5 (4+earth)	2.5mm <sup>2</sup>	2x 1.5mm²	1mm²	0.75mm²	47mm	27.5mm	20mm	4.1mm	drill 3.2mm
CTS4P/12	12	2.5mm <sup>2</sup>	4x 1.5mm²	1mm²	0.75mm²	118mm	21.5mm	17.6mm	-	2.9mm
CTS4P/12S	12	2.5mm <sup>2</sup>	4x 1.5mm²	1mm²	0.75mm²	118mm	21.5mm	17.6mm	-	drill 3.5mm
CTS4P/3ES	3 (2+earth)	2.5mm²	4x 1.0mm²	1mm²	0.75mm²	27.5mm	26.5mm	20.mm	3.2mm	drill 3.2mm







# INTERCONNECTION



#### Strain relief

- Clamps external conductors in lighting fixtures according to EN 60598
- · Natural colour PA6
- · Takes the strain on the wires
- Prevents conductors from twisting


CSR5

 Protects wire coating from abrasion and friction CSR



CSR4

TYPE NO.	CONNECTOR TYPE NO.
CSR4	CTS2P/E & CTS2P/ES
CSR5	CTS4P/ES



LIMIT & SAFETY SWITCHES

> CONTROL PRODUCTS

PCB TERMINAL BLOCKS

INTER-CONNECTION

> FUSES & FUSE-HOLDERS

LEDs & INDICATORS

MINIATURE SWITCHES

INTERFACE MODULES & SUPPORTS

> RELAY BASES

DIN RAIL ENCLOSURES

BATTERIES

SOLAR PANELS

TRANS-FORMERS

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Camden manufacturer:

Other Similar products are found below:

CCTTR30RD 412689X CTBP92VE/12R CTBP9350/12 IND515205-240-T/GRN IND515205-240-T/RD CDIC00002 CCTTBES

C192SHAND RX510A RTM5006/16-PAT CTB9350/12FL CTBP9308/6AO CTBP9358/11 CTBP9208/8 CIME/M/BE2250SS

CHH64E1BL CHD774004 CHHBAT1BK CFTBN/2 RTM5003/13-NAT CCB2S1/04 CCM1S1/05 CHDX7-224C CHDX8-221 CHDX8
222 CHDX8-231C CHDX810DD CHDX811DD CHDX814DD CTB9300/2A CTBP92VD/5R CTBP92VJ/8R CTSN431/12/M

CTSN433/12/M CUABOX012 CDIC00005 CBRPH-BLK BIM2004/LUG-GY/GY RTM5005/15-WH RTM108-BLK CNMB/4/KIT

CTB5050/5 CTBP9358/10AO CTBP93VE/9 CHH66C2GY CIM/9W-DMFS RTM5006/16-NC-BLK IND5032405-125-T/AMB CHTB4/3N