



			Dimer	nsional	tolerar	nce			
Dimension		Lines	r dime	ension	Roundne	Angle			
	With in	Over	Overs	Over30	925	with in	Over)	Over6	
V-1	20.1	20.1	±0.2	±0.3	20.5	±0.2	20.5	*	**
loieronce	±0.2	±0.3	±0.5	±0.8	±1.2	±0.4	±1	#2	±3"





SPECI	FICATIONS
VOLTAGE RATII CURRENT RATI CONDUCTORS: ALU	NGS: 50A
MATERIALS: PE SUITABLE WIRE	
LINE: 2~14	AWG CU
LOND: \$250	
WIRING TORQU	E:
2~3 AWG 4~6 AWG	50 LB-IN 45 LB-IN
	40 LB-IN
LOAD: #250	
CERTIFICATION MA	RIKING: CQC UL CU





HOPPY INDUSTRIAL CO.,LTD.				16.0	08.29	16.08	.29 16.08.29 DWG NO.		HF	HP-AT101-1-3P (H0)							
HODBY INDUSTRIAL OR LTD.					L	.F.	L.W.	S. L.W	L.W.S.								
SCALE		1/1	DIM.	mm	0	À	DR	AWN BY	CHECK	ED	APPROVED BY	TITLE		TERM	INAL BL	OCK	
No.	DATE		CONTEN	π	REVISER	APPROVED	NO.	PART NAME		MATERIAL				Q'TY	FINISH	PART NO.	REMARK
Δ							1	BASE		PF ; UL94V-0				1		ABA1101-1-3P	BLACK
							2	COND	UCTORS	AL	UMINUM	AL6061		3	Sn Plated	AL-1	17
				3	3 WETAL FITTING		BRASS ; t0.8 #250			3	Ni PLATED	PR1-2					
							4	SCR	EW	SS ; 5/16-24UNF				3	JAG3+PLATED	SC311Y	
							5	RIV	ET	CO	PPER ;	7/16-2	OUNF	6	JAG 34PLATED	Ri1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Blockmaster manufacturer:

Other Similar products are found below:

OTB-388-03P-C OTB-359N-02P-C OT-016-M5-L8 HP-ATB-175-5-3P OTB-358N-06P-C HP-ATB-175-4-3P HP-AT-101-1-2P OTB-351-03P-C OTB-388-04P-C OP-487-M6 HP-AT-101-1-3P HB951-23P OTB-351-12P-C OTB-330N-03P-C OTB-351-05P-C OTB-388-02P-C OP-055-M5-L1 OT-201-M8 OP-075-M5 OT-047-M4 675-303/920 OT-048-M5 PSM020H5 MSB03005 KS-03 HI-205-07PH-C 675-102/0 675-302/0