

Wafer Tweezers

The several tip shapes and sizes are designed to handle thin and delicate substrates like glass, metal and silicon wafers while avoiding scratching or breaking of thin layers. Tip sizes are available from 5 to 65 mm width. Teflon coating (full body), plastic tips as well as special designs are available for specific applications.

Anti-Acid/Anti-Magnetic SS (SA)

Anti-Acid/Anti-Magnetic SS (SA) - TEFLON COATING (T)



2WF.SA
Serrated handles. Tips: handling 2", top fingers, stepped bottom paddle. OAL: 120mm




2WFG.SA
Serrated handles. Tips: handling 2", top fingers, stepped bottom paddle with grid. OAL: 120




3WF.SA
Serrated handles. Tips: handling 3", top fingers, stepped bottom paddle. OAL: 125mm



3WFG.SA
Serrated handles. Tips: handling 3", top fingers, stepped bottom paddle with grid. OAL: 125mm



45WF.SA
Serrated handles. Tips: handling 5", top fingers, flat bottom paddle. OAL: 130mm



45WF.SA.T
Teflon coated. Serrated handles. Tips: handling 5", top fingers, flat bottom paddle. OAL: 130mm




48WF.SA
Serrated handles. Tips: handling 6", top fingers, flat bottom paddle. OAL: 135mm




4WF.SA
Serrated handles. Tips: handling 3", top fingers, stepped bottom paddle. OAL: 125mm

Wafer Tweezers



4WFS.A.T

Teflon coated. Serrated handles. Tips: handling 3", top fingers, stepped bottom paddle. OAL: 125mm




4WFG.SA

Serrated handles. Tips: handling 3", top fingers, stepped bottom paddle with grid. OAL 125 mm




5WFS.A

Serrated handles - tips: handling 5", top fingers, stepped bottom paddle. OAL: 130 mm



6WFS.A

Serrated handles. Tips: handling 6", top fingers, stepped bottom paddle. OAL: 130mm




6WFS.A.T

Teflon coated. Serrated handles. Tips: handling 6", top fingers, stepped bottom paddle. OAL: 130mm



8WFS.A

Serrated handles. Tips: handling 6", top fingers, stepped bottom paddle. OAL: 135mm



8WFS.A.T

Teflon coated. Serrated handles. Tips: handling 6", top fingers, stepped bottom paddle. OAL: 135mm



8WNY.SA.1

Serrated handles. Tips: handling 8", top lip, stepped bottom paddle. Nylon tips. OAL: 150mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ideal-Tek](#) manufacturer:

Other Similar products are found below :

[812.01](#) [E5152](#) [BON-102A](#) [4313 SM](#) [5340](#) [35A SA](#) [ST-LED](#) [A242CF](#) [NLP-1](#) [E5234](#) [00.SA.DR](#) [14A.C.DR](#) [15AFW.C](#) [2A.NC](#)
[2AXCPR.SA](#) [3XCF.SA](#) [4.SA.DR](#) [5C.SA.DR](#) [8507](#) [8WNY.SA](#) [AA.SA.DR](#) [ST5-IT-TB](#) [K6PICF](#) [0.SA.0](#) [3C.SA.NE.6](#) [3CPR.SA.1](#)
[AA.SA.DN.6](#) [AM2111](#) [KCFR](#) [56A.SA](#) [PCSA-4](#) [ALCRON](#) [MPTSP5](#) [K5SMD.SA](#) [246CFR.SA](#) [K5HP.SA](#) [5CF.SA](#) [UVO0000100](#) [E5341](#)
[CRBG](#) [A7CP](#) [IT21050](#) [SM108](#) [SM116 SA](#) [248 CF SA](#) [7 SA](#) [E5140](#) [AM4023X](#) [EX2175](#) [361](#) [14AGW.C](#)