

Component positioning Tweezers

Designed specifically to hold delicate components firmly and safely

Anti-Acid/Anti-Magnetic SS (SA)



571.SA
Serrated handles. Tips: straight, grooved, for 2.5-5mm cylindrical device. OAL: 145mm



572.SA
Serrated handles. Tips: straight, grooved, for 2.5-5mm cylindrical device. OAL: 145mm



573.SA
Serrated handles. Tips: straight, grooved, for 2.5-5mm cylindrical device. OAL: 145mm



577.SA
Serrated handles. Tips: straight, grooved, for 2mm cylindrical device. OAL: 125mm



578.SA
Serrated handles. Tips: straight, grooved, for 2mm cylindrical device. OAL: 120mm



582.SA
Serrated handles. Tips: straight, grooved, for 1mm cylindrical device. OAL: 120mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ideal-Tek](#) manufacturer:

Other Similar products are found below :

[812.01](#) [E5152](#) [BON-102A](#) [4313 SM](#) [5340](#) [35A SA](#) [ST-LED](#) [A242CF](#) [NLP-1](#) [E5234](#) [00.SA.DR](#) [14A.C.DR](#) [15AFW.C](#) [2A.NC](#)
[2AXCPR.SA](#) [3XCF.SA](#) [4.SA.DR](#) [5C.SA.DR](#) [8507](#) [8WNY.SA](#) [AA.SA.DR](#) [ST5-IT-TB](#) [K6PICF](#) [0.SA.0](#) [3C.SA.NE.6](#) [3CPR.SA.1](#)
[AA.SA.DN.6](#) [AM2111](#) [KCFR](#) [56A.SA](#) [PCSA-4](#) [ALCRON](#) [MPTSP5](#) [K5SMD.SA](#) [246CFR.SA](#) [K5HP.SA](#) [5CF.SA](#) [UVO0000100](#) [E5341](#)
[CRBG](#) [A7CP](#) [IT21050](#) [SM108](#) [SM116 SA](#) [248 CF SA](#) [7 SA](#) [E5140](#) [AM4023X](#) [EX2175](#) [361](#) [14AGW.C](#)