


# Printed-circuit board connector - FKCOR 2,5/ 8-ST-5,08-LR - 1861755

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug component, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 8, pitch: 5.08 mm, connection method: Push-in spring connection, Color: green, contact surface: Tin



The figure shows a 5-position version

## Why buy this product

- The conductor connection orthogonal to the direction of operation simplifies the cabling of DIN-rail-mountable devices
- Time saving push-in connection, tools not required
- Intuitive use through colour coded actuation lever
- Automatic locking and intuitive release through Lock and Release operating lever in contrasting color
- Can be combined with the MSTB 2,5 range



## Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 100 STK   |
| GTIN                                 | <br>4 055626 125138 |
| GTIN                                 | 4055626125138   |
| Weight per Piece (excluding packing) | 2.220 g   |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |
| Note                                 | Made to Order (non-returnable)  |

## Technical data

### Dimensions

|              |          |
|--------------|----------|
| Length [ l ] | 29.1 mm  |
| Width [ w ]  | 49.64 mm |
| Height [ h ] | 14.7 mm  |
| Pitch        | 5.08 mm  |
| Dimension a  | 35.56 mm |

### General

# Printed-circuit board connector - FKCOR 2,5/ 8-ST-5,08-LR - 1861755

## Technical data

### General

|  |                           |
|--|---------------------------|
| Range of articles                      | FKCOR 2,5/..-ST-LR        |
| Type of contact                        | Female connector          |
| Number of positions                    | 8                         |
| Connection method                      | Push-in spring connection |
| Insulating material group              | I                         |
| Rated surge voltage (III/3)            | 4 kV                      |
| Rated surge voltage (III/2)            | 4 kV                      |
| Rated surge voltage (II/2)             | 4 kV                      |
| Rated voltage (III/3)                  | 250 V                     |
| Rated voltage (III/2)                  | 320 V                     |
| Rated voltage (II/2)                   | 630 V                     |
| Connection in acc. with standard       | EN-VDE                    |
| Nominal current I <sub>N</sub>         | 12 A                      |
| Nominal cross section                  | 2.5 mm <sup>2</sup>       |
| Flammability rating according to UL 94 | V0                        |
| Stripping length                       | 10 mm                     |

### Connection data

|                                       |                     |
|---------------------------------------|---------------------|
| Conductor cross section solid min.    | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.    | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible min. | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max. | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 12                  |

### Standards and Regulations

|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[1212619](#) [3240366](#) [1893300](#) [1401029](#) [1773093](#) [2814045](#) [2989433](#) [2963886](#) [2966537](#) [2313944](#) [2834546](#) [2834407](#) [1687312](#) [3056145](#)  
[1775619](#) [1618261](#) [1674998](#) [2858894](#) [443023](#) [2905235](#) [2833547](#) [3240098](#) [2905234](#) [FFKDS/V-2.54](#) [0201391](#) [0201595](#) [7001438](#)  
[MICROFOX-R](#) [PLC-RSP- 24DC/21-21](#) [PR1-RSC3-LDP-24DC/21](#) [PR1-RSC3-LV-120AC/2X21](#) [PSI-MOS-DNET CAN/FO 660/BM](#) [PSM-](#)  
[SET-FSMA/4-KT](#) [PSR-SCF-120UC/URM/2X21](#) [PT 4-DIO 1N 5408/L-R](#) [PT 4-FSI/F-LED 12](#) [1202580](#) [1203534](#) [1205985](#) [1206308](#) [1201798](#)  
[1207420](#) [1207886](#) [1208461](#) [1208843](#) [1206188](#) [1212066](#) [1212096](#) [1212171](#) [1212250](#)