



Item	Description
VER-28500	Common Point Ground Wire 4.5mL 1 megohm

Specifications

Cord Construction and Material

The body housing shall have a combination of 10mm male snap, 10mm female snap, and banana receptacle with one megohm resistor joined in series while the other end is 10mm female snap. The ground ends of the cord shall have a nylon single material moulding for both moulded body and strain relief.

Conductor: diameter is 2.5mm, with 7 tinsel wires. **Insulation**: straight cord is insulated with PU material

Electrical Properties

The cord conductor shall have an end to end resistance of not greater than 50 ohms.

Resistivity: snap to snap = 1 megohm ± 20% snap to receptacle = 1 megohm ± 20% snap combination to receptacle = 1 megohm ± 20%

Bending Life Test

Exceeds 20,000 cycles of bending life test without any physical damage on the strain relief.

Breakaway Force

1 to 5 lbs. of pull away force is required to disconnect the snap in a normal disconnect direction.

Connection Integrity

The tensile strength of the end connections shall be not less than 66% of the tensile strength of the wire, and in no case shall it be less than 5 lbs.

Colour

Straight cord available in yellow colour, moulded ends and chips in PMS340 green colour.

Hardware

All metal parts shall show no evidence of corrosion and rust after 24 hours submersion to salt solution. Preferably made from stainless steel or brass alloy plated with nickel.

Plastic Parts

Made of antistatic nylon material.

Unless otherwise noted, tolerance ±10% Special manufactured items are not returnable for credit.



Common Point Ground Wire 4.5 mL 1 megohm

VERMASON

UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK

PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk Drawing Number VFR-28500

DATE: December 2015

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MCM manufacturer:

Other Similar products are found below:

NWTBATCAPMB13 25-020 27-505 27-4155 27-840 28-0755 28-5958 50-10820 37-330 PI-UPTIMEUPS 27-5918 27-5977 12-3410 28-6023 55-3230 35SPS-3 28-6008 22-26180 17705 55-5675 27-6020 24-12352 21-7655 28-6017 53-1230 28-5965 21-18966 22-1640 27-4200 83-17607 27-5833 27-5925 24-12344 12-3404 PCM-2100-50 21-19004 28-6080 22-665 24-1040 27-5917 28-6005 55-5670 HD15MM35N-100F 21-4605 21-12825 24-5360 27-4270 27-5940 27-5949 27-6112