DIN Plug with Plastic Handle





Specifications


Rating Insulation Resistance Dielectric Strength Voltage Withstanding Insertion Force Withdrawal Force Contact Resistance Operation Temperature Life Cycle

- :100V AC at 1A or 12V DC 2A Max.
- : Over 100M Ω at 500V DC
- : 250V AC for one minute
- : AC 1000V for one Min.
- : 4 kg Max.
- :1-3.5 kg
- :20m Ω Max.
- : 5°C to 70°C
- : 5000 to 10,000 Times

Materials

Socket Case	: SPCC-SD 0.4/ Nickel Plated
Insulator	: P.B.T
Earth Terminal	: PBSR-H 0.25
Contact Pin	: Bras 0.7/ Silver Plated
Rivet	: AL Nickel Plated

Diagram



Dimensions : Millimetres

Part Number Table

Description	Part Number
DIN Jack, Shielded, 3 Pin	PS000056
DIN Jack, Shielded, 5 Pin	PS000057
DIN Jack, Shielded, 7 Pin	PS000058

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. @Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



X-ON Electronics

Authorized Distributor

Click to view similar products for Pro Signal manufacturer.

Other Similar products are found below :

11998795119988701199887111W3S61106IN1260B24134852413486241562024156212415622241562324156242415625241562624156272415628271450275915277942278076278155278159278160278162278174