



ITEMS:	SPECIFICATION:			VOICE COIL:				
Dimensions	5.25" (140 mm)			Diameter	25.4			(mm)
Impedance	8 ohms	o 111111)		Winding Length	13			(mm)
1				Layer	2			(mm)
Wattage (RMS)	30 W			Former material	Alumin			ASV SVW
Free air resonance	45 Hz 88 dB/W/M, 2.83 V			Wire material		Copper		
Sensitivity				CONE:	Black anodized aluminum con			ne
Frequency range	45 ~ 1200	0 Hz		SURROUND:	Rubbei			
Weight	1480	grams		MAGNET:	(1)	(2	2)	
	1400	gran	15	Diameter	100			(mm)
				Height	19			(mm)
Basket: die cast (aluminum)				Material	ferrite			Y30
Cap: Treated cloth				Quantity	I 500			(pcs)
Shorting ring: Copper				Weight Gap(H)	560 6			(g) (mm)
PARAMETERS:				(11)	U			(11111)
DC resistance	Re:	5.9	(0)	Moving mass		Mms:	10.75	(a)
	Fs:	45.6	(Ω)	Equivalent volume		Vas:	14.54	(g)
Resonance frequency	Zm:	34.8	(Hz)	•		SPL:	87.2	(1)
Maximum impedance Mechanical Q factor	Qms:	34.8 1.976	(Ω)	Sensitivity		Cms:	1.134	(dB)
_	~			Suspension compliance				(mm/N)
Electrical Q factor	Qes:	0.405		BL product	a a4a	Bl:	6.696	(N/A)
Total Q factor	Qts:	0.336		Driver piston diameter		D:	110	(mm)
Linear Displacement	Xmax:	3.5	(mm)	Voice Coil Inductance		Le(1K):	0.72	(mH)
				ce vs Freq				





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MCM manufacturer:

Other Similar products are found below:

NWTBATCAPMB13 25-020 27-505 27-4155 27-840 28-0755 28-5958 50-10820 37-330 PI-UPTIMEUPS 27-5918 27-5977 12-3410 28-6023 55-3230 35SPS-3 28-6008 22-26180 17705 55-5675 27-6020 24-12352 21-7655 28-6017 53-1230 28-5965 21-18966 22-1640 27-4200 83-17607 27-5833 27-5925 24-12344 12-3404 PCM-2100-50 21-19004 28-6080 22-665 24-1040 27-5917 28-6005 55-5670 HD15MM35N-100F 21-4605 21-12825 24-5360 27-4270 27-5940 27-5949 27-6112