

# HGA36040

## PowerPact H I-Line Circuit Breaker, ThermMagn, 40A, 3P, 600V, 18kA

Product availability : Stock - Normally stocked in distribution facility



### Main

|                           |                  |
|---------------------------|------------------|
| Product or component type | Circuit breaker  |
| Range of product          | PowerPact H      |
| Trip unit technology      | Thermal-magnetic |
| Breaking capacity code    | G                |

### Complementary

|   |   |
|---|---|
| Line Rated Current                                  | 40 A  |
| Poles description                                   | 3P  |
| Breaking capacity                                   | 65 kA at 240 V AC<br>35 kA at 480 V AC<br>18 kA at 600 V AC<br>20 kA at 500 V DC<br>20 kA at 250 V DC |
| System Voltage                                      | 500 V DC<br>600 V AC  |
| [Ics] rated service short-circuit breaking capacity | 80 %  |
| Mounting mode                                       | I-Line  |
| Electrical connection                               | I-Line connection line<br>Lugs load   |
| AWG gauge   | AWG 14...AWG 3/0 (aluminium/copper)   |
| Phase connection                                    | ABC   |
| Magnetic hold current                               | 400 A   |
| Magnetic tripping current                           | 850 A   |

### Environment

|                        |           |
|------------------------|-----------|
| Product certifications | IEC<br>CE |
|------------------------|-----------|

UL listed  
CSA

Ambient air temperature for operation 104 °F (40 °C)

### Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 01117 - HG, HJ, JG, JJ I-LINE BREAKER/SWITCH |
| Discount Schedule     | DE2  |
| GTIN                  | 00785901601371                               |
| Nbr. of units in pkg. | 1  |
| Package weight(Lbs)   | 5.410000000000001                            |
| Returnability         | Y  |
| Country of origin     | MX   |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0832 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Schneider manufacturer](#):*

Other Similar products are found below :

[HMIGTO2310](#) [GS1AE21](#) [METSEPM8240](#) [LC1DT25B7](#) [LU9M1](#) [7D](#) [7S](#) [7XA1](#) [8501RS44V24](#) [8501RSD14P14V51](#) [8501XM4](#)  
[8501XO20V03Y414](#) [9001KXRK](#) [9001SKR9P35RH25](#) [9001SKT35L31](#) [9003K2C003GA](#) [9007AA1](#) [9007BA1](#) [9007C54D](#) [9007C62A2](#)  
[9007C68T5](#) [9007CA11](#) [9007FA3](#) [9007HA4](#) [9007HA6](#) [9007KA1](#) [9007KB11](#) [9007MS01S0206](#) [9007MS10S0100](#) [9012GAR4](#) [9012GAW2](#)  
[9012GBW1](#) [9012GDW5E3](#) [9012GFW1](#) [9012GNG1](#) [9012GNG3](#) [9012GNG6](#) [9013FHG39J69](#) [9013GHG2J30](#) [9050JCK2F30V14](#) [GZ1E02](#)  
[A9F07125](#) [ATS01N222RT](#) [ATV12H018F1](#) [RSL1PRJU](#) [9001KA35](#) [9001KA3G](#) [9001KR1GH5](#) [9001KXSDC](#) [9007C52A2](#)