

HJL36050

PowerPact H Circuit Breaker, ThermMagn, 50A, 3P, 600V, 25kA

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact H |
| Trip unit technology | Thermal-magnetic |
| Breaking capacity code | J |

Complementary

| | |
|---|---|
| Line Rated Current | 50 A |
| Poles description | 3P |
| Breaking capacity | 65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC 20 kA at 250 V DC |
| System Voltage | 250 V DC 600 V AC |
| [Ics] rated service short-circuit breaking capacity | 80 % |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load Lugs line |
| AWG gauge | AWG 14...AWG 3/0 (aluminium/copper) |
| Magnetic hold current | 400 A |
| Magnetic tripping current | 850 A |

Environment

| | |
|------------------------|-------------------------------|
| Product certifications | CE IEC UL listed CSA |
|------------------------|-------------------------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------------------|----------------|
| Ambient air temperature for operation | 104 °F (40 °C) |
|---------------------------------------|----------------|

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH |
| Discount Schedule | DE2 |
| GTIN | 00785901839668 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.139999999999997 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0832 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schneider manufacturer](#):

Other Similar products are found below :

[HMIGTO2310](#) [GS1AE21](#) [METSEPM8240](#) [LC1DT25B7](#) [LU9M1](#) [7D](#) [7S](#) [7XA1](#) [8501RS44V24](#) [8501RSD14P14V51](#) [8501XM4](#)
[8501XO20V03Y414](#) [9001KXRK](#) [9001SKR9P35RH25](#) [9001SKT35L31](#) [9003K2C003GA](#) [9007AA1](#) [9007BA1](#) [9007C54D](#) [9007C62A2](#)
[9007C68T5](#) [9007CA11](#) [9007FA3](#) [9007HA4](#) [9007HA6](#) [9007KA1](#) [9007KB11](#) [9007MS01S0206](#) [9007MS10S0100](#) [9012GAR4](#) [9012GAW2](#)
[9012GBW1](#) [9012GDW5E3](#) [9012GFW1](#) [9012GNG1](#) [9012GNG3](#) [9012GNG6](#) [9013FHG39J69](#) [9013GHG2J30](#) [9050JCK2F30V14](#) [GZ1E02](#)
[A9F07125](#) [ATS01N222RT](#) [ATV12H018F1](#) [RSL1PRJU](#) [9001KA35](#) [9001KA3G](#) [9001KR1GH5](#) [9001KXSDC](#) [9007C52A2](#)