

Product availability : Stock - Normally stocked in distribution facility



### Main

|                              |                              |
|------------------------------|------------------------------|
| Range                        | Multi 9                      |
| Product or component type    | Undervoltage release         |
| Device short name            | MN                           |
| [Uc] control circuit voltage | 120 V AC 50/60 Hz<br>24 V DC |
| Control type                 | Standard                     |
| 9 mm pitches                 | 2                            |

### Complementary

|                         |  |
|-------------------------|--|
| Range compatibility     | Multi 9: Multi 9 C60 C60BP<br>Multi 9: Multi 9 C60 C60BPR<br>Multi 9: Multi 9 C60 C60SP<br>Multi 9: Multi 9 GFP GFP<br>Multi 9: Multi 9 C60H-DC C60H-DC                              |
| Local signalling        | Action indicator   |
| Mounting mode           | Fixed  |
| Mounting support        | DIN rail   |
| Height                  | 3.25 in (82.5 mm)  |
| Width                   | 0.71 in (18 mm)  |
| Depth                   | 2.68 in (68 mm)  |
| Product weight          | 0.15 lb(US) (0.066 kg)   |
| Connections - terminals | Clamp terminal bottom 1 cable(s) 0 in <sup>2</sup> (2.5 mm <sup>2</sup> ) rigid (AWG 14)<br>Clamp terminal bottom 2 cable(s) 0 in <sup>2</sup> (1.5 mm <sup>2</sup> ) rigid (AWG 16) |
| Wire stripping length   | 0.35 in (9 mm) bottom  |
| Tightening torque       | 8.85 lbf.in (1 N.m) bottom   |

### Environment

|                        |                              |
|------------------------|------------------------------|
| Standards              | EN 60947-2<br>EN/IEC 60947-1 |
| Product certifications | CSA                          |

UL  
UR  
PCT

|                                       |                            |
|---------------------------------------|----------------------------|
| Pollution degree                      | 3                          |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Ambient air temperature for storage   | -40...185 °F (-40...85 °C) |

### Ordering and shipping details

|                       |                                  |
|-----------------------|----------------------------------|
| Category              | 00948 - M9 GEN 2 CB UL1077 / IEC |
| Discount Schedule     | DE2                              |
| GTIN                  | 00785901761778                   |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 0.16                             |
| Returnability         | N                                |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Schneider manufacturer](#):*

Other Similar products are found below :

[HMIGTO2310](#) [GS1AE21](#) [METSEPM8240](#) [LC1DT25B7](#) [LU9M1](#) [7D](#) [7S](#) [7XA1](#) [8501RS44V24](#) [8501RSD14P14V51](#) [8501XM4](#)  
[8501XO20V03Y414](#) [9001KXRK](#) [9001SKR9P35RH25](#) [9001SKT35L31](#) [9003K2C003GA](#) [9007AA1](#) [9007BA1](#) [9007C54D](#) [9007C62A2](#)  
[9007C68T5](#) [9007CA11](#) [9007FA3](#) [9007HA4](#) [9007HA6](#) [9007KA1](#) [9007KB11](#) [9007MS01S0206](#) [9007MS10S0100](#) [9012GAR4](#) [9012GAW2](#)  
[9012GBW1](#) [9012GDW5E3](#) [9012GFW1](#) [9012GNG1](#) [9012GNG3](#) [9012GNG6](#) [9013FHG39J69](#) [9013GHG2J30](#) [9050JCK2F30V14](#) [GZ1E02](#)  
[A9F07125](#) [ATS01N222RT](#) [ATV12H018F1](#) [RSL1PRJU](#) [9001KA35](#) [9001KA3G](#) [9001KR1GH5](#) [9001KXSDC](#) [9007C52A2](#)