

Part Number: C1361

Revision: 8/7/2017

2C 14 AWG PVC PARALLEL

SPEAKER WIRE

A. CONSTRUCTION

DIAMETERS

Conductor (Leg 1):	#14 AWG (41/30) Tinned Copper	.048" Nom
Conductor (Leg 2):	#14 AWG (41/30) Bare Copper	.048" Nom
Insulation:	.025" Wall, Polyvinly Chloride (PVC)	.130" x .270" Nom
Ripcord:	None	
Sequential Footage:	None	
Print Legend:	<i>CAROL (R) 14 AWG C1361 - E54567-8 (UL) 120 VOLT SPEAKER WIRE</i>	

B. INDUSTRY APPROVALS

UL Listed (Misc.)	Speaker Wire
EU Directive 2011/65/EU (RoHS-2)	RoHS Compliant

C. ELECTRICAL PROPERTIES

Temperature:	0°C to +60°C
Suggested Working Voltage:	120 Vrms (Max)
Conductor DCR (TC):	2.73 Ohms/1000ft (Nom) @ 20°C
Conductor DCR (BC):	2.62 Ohms/1000ft (Nom) @ 20°C

D. COLOR CODE

Contact Customer Service for color options

E. CUSTOMER APPROVAL

Signature: _____

Date: _____

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Carol manufacturer:

Other Similar products are found below :

[01364.35T.01](#) [01776.38.01](#) [76843.38.06](#) [C0754A.21.10](#) [C1670A.41.10](#) [C2015A.12.04](#) [C2015A.12.19](#) [C2526A.18.10](#) [C3120.18.86](#)
[C4066A.38.10](#) [01104.99.01](#) [01343.35T.01](#) [5133290E](#) [2133033](#) [83350.99.01](#) [2133016](#) [16065.41.01](#) [5131431E](#) [09814.99.01](#) [E2206S.41.86](#)
[E1524S.41.03](#) [E2534S.41.03](#) [C0560A.41.10](#) [C2016A.12.03](#) [C2064A.12.02](#) [C2103A.12.03](#) [C2105A.12.02](#) [C0570A.41.10](#) [C1302.41.01](#)
[C1343A.41.10](#) [C1357.41.90](#) [C2405A.41.10](#) [C3120.41.86](#) [C0432A.41.10](#) [C1352A.41.10](#) [C2536A.38.10](#) [E2204S.41.02](#) [E3612S.41.03](#)
[C1644A.18.10](#) [C5775.27.01](#) [E2102S.30.86](#) [E1032S.25.10](#) [02604.41T.05](#) [02605.41T.05](#) [02608.41T.05](#) [02634.35T.05](#) [02634.41T.05](#)
[02601.41T.05](#) [E1032S.41.10](#) [E2024S.41.10](#)