



Tenma 72-10390

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2000mV/20V/200V/250V	$\pm(0.5\%+2)$
AC Voltage	200V/250V	$\pm(1.2\%+3)$
DC Current	2000 μ A/20mA/200mA/10A	$\pm(1\%+2)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2000k Ω /20M Ω	$\pm(1.2\%+3)$
Temperature($^{\circ}$ C)	-40 $^{\circ}$ C~1000 $^{\circ}$ C	$\pm(1.0\%+3)$
Special Functions		
Display Count		1999
Manual Range		√
Diode		√
Transistor		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
Input Impedance for DCV	Around :10M Ω	√

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)	
LCD Size	49 x 18mm	
Product Colour	Orange and Grey	
Product Net Weight	200g	
Product Size	72 x 137 x 35mm	
Standard Accessories	Battery, Test Lead, Multi-Purpose Socket, Point Contact Temperature Probe	
Standard Individual Packing	Gift Box , English Manual	
Standard Quantity Per Carton	40pcs	
Standard Carton Measurement	540 x 365 x 290mm(0.057 CBM Per Standard Carton)	
Standard Carton Gross Weight	13.8kg	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tenma](#) manufacturer:

Other Similar products are found below :

[76-080](#) [76-355](#) [CBB018722](#) [72-3500](#) [76-021](#) [76-077](#) [72-13668](#) [72-13686](#) [72-13736](#) [72-13742](#) [72-13750](#) [72-13798](#) [72-13818](#) [72-13820](#) [72-13822](#) [72-13824](#) [72-13836](#) [72-13858](#) [72-13926](#) [72-13950](#) [72-14096](#) [72-14112](#) [72-14280](#) [72-14302](#) [72-14304](#) [72-14342](#) [AT980D UK](#) [21-10156](#) [72-2655](#) [BC0019213](#) [76-004A](#) [76-024](#) [A1170](#) [72-14530 EU](#) [72-13654](#) [72-13664](#) [72-13774](#) [72-13872](#) [72-13874](#) [72-13888](#) [72-13986](#)
[72-14014](#) [72-14044](#) [72-14118](#) [72-14272](#) [72-14316](#) [21-10152](#) [72-10405](#) [CBB019217](#) [72-9490](#)