



NOTES:

1. MATERIALS

1.1 CABLE: (7/0.12BC)*1P+(7/0.20BC+PVC)*2C+AL
 +7/0.12BC+64/0.12ALM+BLACK PVC JACKET.
 OD=∅4.5±0.15MM.

CABLE MARKING:USB 2.0 CABLE FULLY RATED 30V 80°C

1.2 CONNECTOR: P1: USB A TYPE MALE: SOLDER TYPE,
 GOLD FLASH CONTACTS, NICKEL PLATED SHELL.

1.3 P2: USB2.0 MINI 5P B MALE: SOLDER TYPE,
 GOLD FLASH CONTACTS, NICKEL PLATED SHELL.

1.4 ALL HOOD: MOLDED BLACK PVC.

2. 100% OPEN AND SHORT TEST.

3. PACKING:1PCS/PE BAG.

4. ALL MATERIAL BE RoHS COMPLIANT.

PIN OUT

P1 ——— P2

1 ——— 1 RED
 2 ——— 2 WHITE
 3 ——— 3 GREEN
 4 ——— 4 BLACK

SHELL ——— SHELL (BRAID+DRAIN)

——— > PAIR



LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1	SCALE: FREE	CUS. NAME: CPC	PRODUCT NO:		ENG: SUMIN
	UNIT: mm		CUSTOMER NO: 83-10706		CHECKED:
ANGLE TOLERANCE: X° ± 3° .X° ± 1°	VERSION: 00	DRAWING NO: 1572	PRODUCT DESCRIPTION: USB2.0 AM/MINI 5P BM		APPROVED:
	PAGE: 1/1				

00	NEW ISSUE	2018-1-3
REV.	MODIFY DESCRIPTION	DATE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MCM manufacturer](#):

Other Similar products are found below :

[NWTBATCAPMB13](#) [25-020](#) [27-505](#) [27-4155](#) [27-840](#) [28-0755](#) [28-5958](#) [50-10820](#) [37-330](#) [PI-UPTIMEUPS](#) [27-5918](#) [27-5977](#) [12-3410](#) [28-6023](#) [55-3230](#) [35SPS-3](#) [28-6008](#) [22-26180](#) [17705](#) [55-5675](#) [27-6020](#) [24-12352](#) [21-7655](#) [28-6017](#) [53-1230](#) [28-5965](#) [21-18966](#) [22-1640](#) [27-4200](#) [83-17607](#) [27-5833](#) [27-5925](#) [24-12344](#) [12-3404](#) [PCM-2100-50](#) [21-19004](#) [28-6080](#) [22-665](#) [24-1040](#) [27-5917](#) [28-6005](#) [55-5670](#)
[HD15MM35N-100F](#) [21-4605](#) [21-12825](#) [24-5360](#) [27-4270](#) [27-5940](#) [27-5949](#) [27-6112](#)