	WASSESSESSESSESSESSESSESSESSESSESSESSESSE		contraction to activities activities of
	CABLE S	SPECIF	FICATION
SPEC NO.:	RG6/U CCS COAXIAL	CABLE	
	Custome	er No.	24-10211
Construc	tion Item	Unit	Construction Item
	Construction	mm	$1/1.02\pm0.05$
Conductors	Material		CCS
Conductors	Filler Material		
	0. D.	mm	$1.02\pm0.05$
Insulators	Material		Foamed PE
	Diameter	mm	4.57±0.01
	Average Thickness	mm	1.77±0.05
	Colour	1000	White
	AL-PET Foil	um	AL-P-AL
Outer Conductors	Type		Braid
	Material		ALMG
	Coverage	%	60%
	Diamater	mm	$4.80\pm0.15$
	Material		PVC (CM)
Jacket	Diameter	mm	$6.90\pm0.15$
	Average Thickness	mm	$1.00\pm0.10$
	Extrusion		_
	Surface		
	Colour	1000	White
Inking	Inking Colour		Black
	Inking	-	Stellar Labs RG6/U TYPE COAX 750HM 18AWG 75degC 2250MHz E188601 (UL) CM ROHS COMPLIANT
Line	Length	ft	1000
CONFIGURATI			Conductor Al Foil ALMG Braid Insulator Jacket
GENERAL TOLERANCI (UNLESS SPECIFIED	201	5	tellar@ <sub>Labs™</sub>
LENGTH: X. ±1 . X±0. 2 . XX±0. 10	UNIT:mm REV: DRAWING XIAOSHENG 2008/10	0/07 S.P.	NAME RG6/U CCS COAXIAL CABL
ANGLE: X° . ±1°	CHECK CHECK	P. 0.	NO. DWG. NO.
. X° ±0°	APPROVE APPROVE	SI	ZE PAGE 1/1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for STELLAR LABS manufacturer:

Other Similar products are found below:

24-15099 24-16210 24-16211 24-10220 JR8306A-3M 555-13890 83-9962 24-15450 24-15453 24-16053 24-16063 24-16135 24-16147
24-15452 24-15455 24-15942 24-15984 24-15989 24-16012 24-16049 24-833 24-1810 83-16411 10DV-07203-R 24-15411 24-15435 2415456 24-15396 24-15061 24-15053 24-15085 24-15158 24-15951 24-15959 24-16041 24-16058 24-16145 24-1850 24-1830 24-1855
83-12261 24-12307 24-15418 33-10915 24-10271 24-15413 24-15417 24-15433 24-15439 24-15393