

PRODUCT SPECIFICATIONS

28-21490 Three (3) outlet Power Supply Cord



| Technical Specifications Maximum Input Voltage (VAC) Nominal Input Frequency (Hz) Maximum Output Power (Watts) Maximum Line Current (Amps) | 60 1625W |
|--|---|
| Regulatory Compliance (needed on all models) Standard | UL 817 ETL & CETL SPT-2 16AWG/3C 60°C |
| Physical Specifications Exterior Dimensions (mm) Enclosure Material Housing Colors Top Bottom Housing Exterior Enclosure Containment Design Outlets Outlet Design Total Number | ABS / Plastic UL94V-0whitedull polishultrasonic welding3 holes grounded |
| Environmental Operating Temperature Conditions of Operation Product/Component Performance and Periodic Auditory UL 817 UL 498 | RequirementsYes |
| UL Markings Requirements Product Back Housing Label and / or Mold UL or ETL File number of manufacturer Electrical rating in volts and amperes | Yes |

Product specification of LTS-B5 3 Outlets Power Supply Cords.....

| Electrical Test | | | | | |
|--|--------------------------|---------------------|--|--|--|
| Max Input voltage | | Rated 1 minute | 132Vac, no damage | | |
| Power switch function | | Power ON | NA | | |
| Output rating | | | 125V 15A 1875W | | |
| Receptacle / Outlet mechanical test (Sampling) | | | | | |
| Withdraw force | after10 insertion cycles | w 3 prongs plug | 15 LB max | | |
| Retention force | | w 2 prongs plug | 3 LB min., 1 minute, displacement < 2 mm | | |
| | | | | | |
| Safety test | | | | | |
| Hi Pot test | | 1250Vac | 1 minute, No breakdown | | |
| Leakage current test | | L to G | 0.5 mA max | | |
| | | N to G | 0.5 mA max | | |
| Insulation resistance | | AC input to USB O/P | 100 m ohm max | | |
| | | <u> </u> | | | |

Product Markings



Revisions:

| INCVISIONS. | | | | |
|-------------|-----------------------|-----------|-------------|--|
| Rev | Description of change | Date | Approved By | |
| | | MM/DD/YY | Initials | |
| NR | Original | 3/16/2016 | Ding | |
| | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for STELLAR LABS manufacturer:

Other Similar products are found below:

24-15099 24-16210 24-16211 24-10220 JR8306A-3M 555-13890 83-9962 24-15450 24-15453 24-16053 24-16063 24-16135 24-16147
24-15452 24-15455 24-15942 24-15984 24-15989 24-16012 24-16049 24-833 24-1810 83-16411 10DV-07203-R 24-15411 24-15435 2415456 24-15396 24-15061 24-15053 24-15085 24-15158 24-15951 24-15959 24-16041 24-16058 24-16145 24-1850 24-1830 24-1855
83-12261 24-12307 24-15418 33-10915 24-10271 24-15413 24-15417 24-15433 24-15439 24-15393