## 09 12 240 T

## Lineman's Pliers with tether attachment point

## American style







- Improved version
- Now requires 50% less effort compared with conventional combination pliers due to an optimised transmission ratio
- Solid construction for heaviest strain; universally applicable
- Ergonomically optimised handle shape for firm contact to the hand and fatigue reducing operation
- Particularly effective cross-hatched knurled gripping zone in the jaws - for strong gripping and pulling
- Additional gripping zone below the joint for powerful leverage and pressing performance
- With cutting edges for soft and hard wire
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Vanadium electric steel, forged, multi stage oil-hardened
- With fish tape puller in the joint gap
- With universal mandrel crimping point below the joint
- Pliers with tether attachment point for mounting a fall protection

Article No.	09 12 240 T
EAN	4003773079958
Pliers	black atramentized
Head	polished
Handles	with multi-component grips and integrated tether attachment point
Cutting capacities medium hard wire (diameter) Ø mm	4,6
Cutting capacities hard wire (diameter) Ø mm	3,0
Length mm	240
Net weight g	455



Gripping zone below the Cross-hatched, knurled joint for powerful leverage



gripping zone for firm gripping and pulling, e. g. for fence construction



Long cutting edges for cutting flat cables

technical change and errors excepted

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Knipex manufacturer:

Other Similar products are found below:

11 06 160 T 00 21 41 LE 76 12 125 78 23 125 86 03 400 88 06 250 92 22 13 9503 160 SB 95 12 500 95 31 250 95 62 190 97 49 14 97 49 15 97 51 10 13 02 160 14 26 160 26 16 200 26 26 200 94 15 215 95 26 165 97 52 04 97 53 08 97 90 10 98 03 06 98 03 11 98 53 13 16 29 165 35 62 145 34521330ESD 48 11 J0 49 11 A0 0301160 11 17 160 71 22 200 87 03 250 00 20 18 ESD 98 33 50 97 91 01 97 49 24 49 11 A4 49 21 A41 95 32 320 95 32 315 A 79 52 125 ESD 79 52 125 1660100SB 98 65 41 97 49 50 97 49 06 95 36 315 A