



## Miniature circuit breaker (MCB), 4A, 2p, type B characteristic

**Part no.** FAZ-B4/2  
**Catalog No.** 278726  
**Eaton Catalog No.** FAZ-B4/2  
**EL-Nummer (Norway)** 1691019

Similar to illustration

## Delivery program

|   |       |    |  |
|---|-------|----|--|
| Basic function                                  |       |    | Miniature circuit-breakers                                     |
| Number of poles                                 |       |    | 2 pole   |
| Tripping characteristic                         |       |    | B  |
| Application                                     |       |    | Switchgear for industrial and advanced commercial applications |
| Rated current                                   | $I_n$ | A  | 4  |
| Rated switching capacity acc. to IEC/EN 60947-2 |       | kA | 15   |
| Product range                                   |       |    | FAZ  |

## Technical data

### Electrical

|   |       |      |                                |
|---|-------|------|--------------------------------|
| Standards                                       |       |      | IEC/EN 60947-2<br>IEC/EN 60898 |
| Rated operational voltage                       | $U_e$ | V    |                                |
|   | $U_e$ | V AC | 240/415                        |
| Rated switching capacity acc. to IEC/EN 60947-2 |       | kA   | 15                             |

## Design verification as per IEC/EN 61439

|  |            |    |   |
|--|------------|----|---|
| Technical data for design verification   |            |    |   |
| Rated operational current for specified heat dissipation   | $I_n$      | A  | 4   |
| Heat dissipation per pole, current-dependent   | $P_{vid}$  | W  | 0   |
| Equipment heat dissipation, current-dependent  | $P_{vid}$  | W  | 2.9   |
| Static heat dissipation, non-current-dependent   | $P_{vs}$   | W  | 0   |
| Heat dissipation capacity  | $P_{diss}$ | W  | 0   |
| Operating ambient temperature min.   |            | °C | -40   |
| Operating ambient temperature max.   |            | °C | 75  |
|  |            |    | linear, per +1 °C, results in a 0.5% reduction of current carrying capacity |
| IEC/EN 61439 design verification   |            |    |   |
| 10.2 Strength of materials and parts   |            |    |   |
| 10.2.2 Corrosion resistance  |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.2.3.1 Verification of thermal stability of enclosures   |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.2.5 Lifting   |            |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |            |    |   |
| 10.2.6 Mechanical impact   |            |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |            |    |   |
| 10.2.7 Inscriptions  |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.3 Degree of protection of ASSEMBLIES  |            |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |            |    |   |
| 10.4 Clearances and creepage distances   |            |    |   |
| Meets the product standard's requirements.   |            |    |   |
| 10.5 Protection against electric shock   |            |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |            |    |   |
| 10.6 Incorporation of switching devices and components   |            |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |            |    |   |
| 10.7 Internal electrical circuits and connections  |            |    |   |
| Is the panel builder's responsibility.   |            |    |   |
| 10.8 Connections for external conductors   |            |    |   |
| Is the panel builder's responsibility.   |            |    |   |
| 10.9 Insulation properties   |            |    |   |
| 10.9.2 Power-frequency electric strength   |            |    |   |
| Is the panel builder's responsibility.   |            |    |   |
| 10.9.3 Impulse withstand voltage   |            |    |   |
| Is the panel builder's responsibility.   |            |    |   |

|  |  |  |
|--|--|--|
| 10.9.4 Testing of enclosures made of insulating material |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 6.0

|  |    |         |
|--|----|---------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)   |    |         |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecI@ss8.1-27-14-19-01 [AAB905011]) |    |         |
| Release characteristic   |    | B       |
| Number of poles (total)  |    | 2       |
| Number of protected poles  |    | 2       |
| Nominal rated current  | A  | 4       |
| Nominal rated voltage  | V  | 400     |
| Rated short-circuit breaking capacity Icn EN 60898 at 230 V  | kA | 10      |
| Rated short-circuit breaking capacity Icn EN 60898 at 400 V  | kA | 10      |
| Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V   | kA | 15      |
| Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V   | kA | 15      |
| Voltage type   |    | AC      |
| Current limiting class   |    | 3       |
| Frequency  | Hz | 50 - 60 |
| Concurrently switching N-neutral   |    | No      |
| Suitable for flush-mounted installation  |    | No      |
| Over voltage category  |    | 3       |
| Pollution degree   |    | 2       |
| Width in number of modular spacings  |    | 2       |
| Built-in depth   | mm | 70.5    |
| Additional equipment possible  |    | Yes     |
| Degree of protection (IP)  |    | IP20    |

## Approvals

|                                  |  |  |
|----------------------------------|--|--|
| Product Standards                |  | IEC/EN 60947-2; IEC/EN 60898; UL 1077; CSA-C22.2 No. 235; CE marking |
| UL File No.                      |  | E177451  |
| UL Category Control No.          |  | QVNU2, QVNU8   |
| CSA File No.                     |  | 204453   |
| CSA Class No.                    |  | 3215-30  |
| North America Certification      |  | UL recognized, CSA certified   |
| Conditions of Acceptability      |  | Supplementary Protector only   |
| Suitable for                     |  | Branch Circuits; not as BCPD   |
| Current Limiting Circuit-Breaker |  | No   |
| Max. Voltage Rating              |  | 480Y/277 VAC; 96 VDC   |
| Degree of Protection             |  | IEC: IP20; UL/CSA Type: -  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circuit Breakers](#) category:*

*Click to view products by [Eaton](#) manufacturer:*

Other Similar products are found below :

[M39019/04-249S](#) [M39019/04-313S](#) [M55629/1-001](#) [M55629/1-016](#) [M55629/1-018](#) [M55629/1-021](#) [M55629/1-033](#) [M55629/1-036](#) [M55629/1-046](#) [M55629/1-048](#) [M55629/1-058](#) [M55629/1-060](#) [M55629/1-067](#) [M55629/1-070](#) [M55629/1-079](#) [M55629/1-084](#) [M55629/1-085](#) [M55629/1-101](#) [M55629/1-108](#) [M55629/1-109](#) [M55629/11-102](#) [M55629/1-120](#) [M55629/12-045](#) [M55629/12-046](#) [M55629/1-243](#) [M55629/1-330](#) [M55629/1-331](#) [M55629/1-351](#) [M55629/1-366](#) [M55629/1-387](#) [M55629/1-388](#) [M55629/1-401](#) [M55629/1-430](#) [M55629/1-450](#) [M55629/1-453](#) [M55629/2-022](#) [M55629/2-037](#) [M55629/2-082](#) [M55629/2-099](#) [M55629/2-101](#) [M55629/2-102](#) [M55629/2-115](#) [M55629/2-116](#) [M55629/2-183](#) [M55629/21-HM-HM](#) [M55629/21-NS-NS](#) [M55629/21-SK-UK](#) [M55629/22-NR-NR-NR](#) [M55629/22-RS-RS-RS](#) [M55629/22-TM-TM-TM](#)