Rubber Covered Neodymium (NdFeB) Pot Magnets

- Internal Thread

Strong Holding Force, resistant to corrosion, protects against surface damage

The arrangement of magnets and the rubber coating is ideal for use on surfaces which should not be scratched and / or where movement or slippage of a normal metal pot magnet system is a problem. This makes its use recommended for painted or varnished articles, or for applications where a strong magnetic force is needed, without marking or scratching surfaces.

The multi-pole structure of the magnets ensures a dense magnetic field on the holding surface. This allows good holding on thin surface eg. lacquered car body metal. The side displacement forces are extremely good due to the suction effect of the rubber surface.

The rubber protects the magnet in humid conditions where corrosion is likely. The holding force is not weakened even after years of use.



Product Information

Product Number	Diameter mm	Thickness mm	Thread Size	Holding Force kg	Units / Pack
E851/2	22	6	M4	5	2
E853/2	43	6	M4	8.5	2
E854/2	66	8.5	M5	18	2
E855/2	88	8.5	M6	42	2

www.eclipsemagnetics.com

Eclipse Magnetics Ltd, Atlas Way, Sheffield, S4 7QQ, England T +44 (0)114 225 0600 F +44 (0)114 225 0525 E info@eclipsemagnetics.com

While every effort has been made to ensure the accuracy of the information in this publication please note that specifications may change without notice.







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Eclipse manufacturer:

Other Similar products are found below:

E891 E890 N822 MRT810T 5MT-7600-LC 902-340 E771NEO E1003/NEO FM662 E774NEO N820 N852N NH025 N806 N854S E998/NEO 828 831 FM663 E761NEO E1004/NEO E872 N815 122 N859 E805 E1000/NEO E862 E772NEO/F E756NEO N818 NH065 N854N E1023/NEO MRT625MFF E892 N850N FM699 E905/F NH130 E853/2 834 E876 E881 N862 E906/F E1002/NEO N851S E1014/NEO E855/2