

# Magnetic Contact

## CATALOG

*For All Your Security Needs*



### Overhead Door Magnetic Contacts

**SM-226LQ\*** N.C.  
**SM-226L-3Q** NO/NC



- Gold and deactivated rhodium plating for longer life
- Switch contained in curved, low-profile, cast-aluminum housing, magnet in gray ABS case on L-bracket
- 24" (61cm) Wire leads enclosed in armored cable
- 2¾" (70mm) Gap



**SM-226RQ\*** N.C.  
**SM-226R-3Q** NO/NC



- Gold and deactivated rhodium plating for longer life
- Switch contained in curved, low-profile, cast-aluminum housing, magnet enclosed in round bracket
- 24" (61cm) Wire leads enclosed in armored cable
- 2¾" (70mm) Gap



**SM-4201-LQ** N.C.



- Industrial, overhead door, track mount
- Rugged aluminum housing
- Adjustable to fit most door-channel widths
- 36" (91cm) Wire leads enclosed in armored cable
- 3" (76mm) Gap



**SM-4601-LQ\*** N.C.  
**SM-4601-L3Q** NO/NC



- Industrial, wide gap, surface mount
- Rugged aluminum housing
- Weatherproof and sealed for outdoor use
- 36" (91cm) Wire leads enclosed in armored cable
- 3" (76mm) Gap



## Surface-Mount Magnetic Contacts

**SM-200Q/W\*** *White, N.C.*  
**SM-200Q/BR\*** *Brown, N.C.*



- Standard surface mount
- Gold and deactivated rhodium plating for longer life
- Includes terminal cover
- ¾" (19mm) Gap



**SM-300Q/W\*** *White, N.O.*  
**SM-300Q/BR\*** *Brown, N.O.*



- Standard surface mount
- Gold and deactivated rhodium plating for longer life
- Includes terminal cover
- For N.O. circuits
- ¾" (19mm) Gap



**SM-431-TQ/W\*** *White, N.C.*  
**SM-431-TQ/B\*** *Brown, N.C.*



- Miniature surface mount
- Gold-plated terminals for longer life
- Screw mount using side flanges, or adhesive mount (mounting screws and double-sided tape included)
- 1" (25mm) Gap



**SM-4003-TQ/W** *White, N.C.*

- Miniature surface mount
- Gold-plated terminals for longer life
- Adhesive mount (double-sided tape included)
- 1" (25mm) Gap



**NEW**

**SM-433-TQ/W\*** *White, N.C.*  
**SM-433-TQ/B\*** *Brown, N.C.*



- Surface-mount contact
- Gold-plated terminals for longer life
- Cover hides mounting screws, terminal block, and wires
- 1 7/32" (31mm) Gap



**SM-4004-TQ/W** *White, N.C., terminals*  
**SM-4004-LQ/W** *White, N.C., leads (18" / 46cm)*

- Miniature "capsule-type" surface mount
- Gold-plated terminals for longer life
- Adhesive mount (tape included)
- ¾" (19mm) Gap - SM-4004-LQ
- 1" (25mm) Gap - SM-4004-TQ



**NEW**

**SM-204Q/W\*** *White, N.C.*  
**SM-204Q/BR\*** *Brown, N.C.*



- Miniature "flange-type" surface mount
- Gold and deactivated rhodium plating for longer life
- Screw mount using flanges, or adhesive mount (double-sided tape included); flanges are removable
- 15" (38cm) Leads extend from center
- 1" (25mm) Gap



**SM-205Q/W\*** *White, N.C.*  
**SM-205Q/BR\*** *Brown, N.C.*



- Miniature "flange-type" surface mount
- Gold and deactivated rhodium plating for longer life
- Screw-mount using flanges, or adhesive mount (double-sided tape included); flanges are removable
- 15" (38cm) Leads extend from side
- 1" (25mm) Gap



**SM-216Q/GY\*** *Gray, N.C.*  
**SM-216Q/BR\*** *Brown, N.C.*



- Wide-gap surface mount for loose-fitting doors and windows
- Gold and deactivated rhodium plating for longer life
- Includes spacers
- 2 3/4" (70mm) Gap




**SM-217Q/W** *White, N.C.*

- Miniature wide-gap surface mount for loose-fitting doors and windows
- Gold and deactivated rhodium plating for longer life
- Wide gap, yet contact is no longer than conventional surface type
- 2" (51mm) Gap




\* Indicates UL-Listed products

## Recessed-Mount Magnetic Contacts

**SM-4102-TQ/W\*** *White, N.C.*  **NEW**


- 3/8" Press-fit mount
- Gold-plated terminals for longer life
- Switch and magnet have ribs for securing in holes
- 1" (25mm) Gap



**SM-407-5TQ/W\*** *White, N.C.* 

- 3/8" Press-fit mount with stubby magnet
- Gold-plated terminals for longer life
- Switch and magnet have ribs for securing in holes
- 3/4" (19mm) Gap



**SM-207Q/W\*** *White, N.C.*   
**SM-207Q/BR\*** *Brown, N.C.*


- 3/8" Press-fit mount
- Gold and deactivated rhodium plating for longer life
- Unique glue/epoxy compound protects reed switch
- Switch and magnet have ribs for securing in holes
- 15" (38cm) Wire leads
- 1" (25mm) Gap



**SM-207-5Q/W** *White, N.C.*  
**SM-207-5Q/BR** *Brown, N.C.*


- Similar to SM-207Q but with stubby 3/4" (19mm) magnet and switch
- 3/8" (10mm) Gap



**SM-206Q/W\*** *White, N.C.*   
**SM-206Q/BR\*** *Brown, N.C.*

- 1/4" Press-fit mount
- Gold and deactivated rhodium plating for longer life
- Unique glue/epoxy compound protects reed switch
- 15" (38cm) Wire leads
- 1" (25mm) Gap



**SM-207-5LQ/W\*** *White, N.C.*   
**SM-207-5LQ/BR\*** *Brown, N.C.*


- Similar to SM-207Q but with stubby 3/4" (19mm) switch
- 1" (25mm) Gap



**SM-4103-TQ/W** *White, N.C.* **NEW**


- 3/8" Press-fit mount with stubby 1" (25mm) switch
- Gold-plated terminals for longer life
- Rare-earth magnet with nickel plating to protect against chipping and corrosion
- Switch has ribs for securing in hole
- 1/2" (13mm) Gap



**SM-4103-LQ/W\*** *White, N.C.*  **NEW**


- Similar to SM-4103-TQ/W but with 18" (46cm) wire leads



**SM-4104-TQ/W\*** *White, N.C.*  **NEW**

- 3/4" (19mm) Steel-door recessed mount
- Gold-plated terminals for longer life
- Strong one-piece construction
- Switch and magnet have ribs for securing in hole
- 1" (25mm) Gap (on steel)



**SM-4105-LQ/W\*** *White, N.C.*  **NEW**  
**SM-4105-LQ/B\*** *Brown, N.C.*

- Similar to SM-4104-TQ/W but with 18" (46cm) wire leads



\* Indicates UL-Listed products

## Plunger-Type Magnetic Switches

### SM-4301-TQ/W\* White, N.C.



- Pushbutton
- Magnet and reed switch contained in housing
- Spacer and screws included
- Quick-connect terminals
- Roller travel is 1/4" (6mm)



### SM-4303-TQ/W\* White, N.C.



- Quick-connect terminals
- 360° Rollerball
- Magnet and reed switch contained in housing
- Spacer and screws included
- Roller travel is 1/4" (6mm)



### SM-4302-LQ/W\* White, N.C.



- 18" (46mm) Wire leads
- 360° Rollerball
- Magnet and reed switch contained in housing
- Spacer and screws included
- Roller travel is 1/4" (6mm)



## Accessories

### SM-831

Alnico 5 magnet,  
1/4" (32mm) length x  
1/4" (6mm) diameter



### SM-841

Alnico 5 magnet,  
1 5/8" (41mm) length x  
3/8" (10mm) diameter



### SM-851

Aluminum "Z" bracket  
for SM-216Q/SM-226LQ



### SM-852LQ

Aluminum "L" bracket  
for SM-216Q/SM-226LQ



\* Indicates UL-Listed products

**WARRANTY:** This SECO-LARM product is warranted against defects in material and workmanship while used in normal service for the lifetime of the product. SECO-LARM's obligation is limited to the repair or replacement of any defective part if the unit is returned, transportation prepaid, to SECO-LARM. This Warranty is void if damage is caused by or attributed to acts of God, physical or electrical misuse or abuse, neglect, repair or alteration, improper or abnormal usage, or faulty installation, or if for any other reason SECO-LARM determines that such equipment is not operating properly as a result of causes other than defects in material and workmanship. The sole obligation of SECO LARM and the purchaser's exclusive remedy, shall be limited to the replacement or repair only, at SECO-LARM's option. In no event shall SECO-LARM be liable for any special, collateral, incidental, or consequential personal or property damage of any kind to the purchaser or anyone else.

**NOTICE:** The information and specifications printed in this catalog are current at the time of publication. However, the SECO-LARM policy is one of continual development and improvement. For this reason, SECO-LARM reserves the right to change specifications without notice. SECO-LARM is also not responsible for misprints or typographical errors. Copyright © 2015 SECO-LARM U.S.A., Inc. All rights reserved. This material may not be reproduced or copied, in whole or in part, without the written permission of SECO-LARM.

## SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606  
Phone: (949) 261-2999 | (800) 662-0800

Website: [www.seco-larm.com](http://www.seco-larm.com)  
Email: [sales@seco-larm.com](mailto:sales@seco-larm.com)

  
MagneticContactCatalog\_150529.  
indd

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [SECO-LARM](#) manufacturer:*

Other Similar products are found below :

[SS-090-2H1](#) [ST-2406-5A](#) [SL-1301-BAQ/C](#) [SA-027WQ](#) [SD-7202GC-PT](#) [SL-1301-BAQ/B](#) [SM-4105-LQ/B](#) [82-12781](#) [E-936-S45RRGQ](#) [SM-4103-TQ/W](#) [E-941SA-1200](#) [SD-7201GCPE1Q](#) [SK-990AQ](#) [SS-090-2H0](#) [SM-226R-3Q](#) [SD-7202GC-PEQ](#) [E-941SA-300RQ](#) [SM-4104-TQ/W](#) [SM-205Q/BR](#) [SR-1212-C2ALQ](#) [SM-4601-LQ](#) [SA-025Q](#) [SL-126Q/C](#) [SM-200Q/BR](#) [CA-1615-06LQ](#) [SS-074Q/BG](#) [CA-1515Q](#) [SM-4201-LQ](#) [SK-91ERSD](#) [SM-4303-TQ/W](#) [SK-1011-SDQ](#) [SM-216Q/GY](#) [NE-SE01-020Q](#) [CA-1610-3FLQ](#) [NJ-P101M-PQ](#) [SM-226RQ](#) [SS-073Q](#) [SL-126Q/R](#) [SL-126Q/A](#) [SL-1312-SA/R](#) [SL-126Q/B](#) [SM-204Q/W](#) [SM-207-5Q/BR](#) [SM-4102-TQ/W](#) [SM-4301-TQW](#) [CA-1616Q](#) [SM-4601-L3Q](#) [SL-1301-BAQ/R](#) [SM-226LQ](#) [SM-226L-3Q](#)