


High-Temperature Inconel® Overbraided Silica Fiber Insulated Thermocouples



- ✓ High-Temperature Insulation with Inconel Overbraid
- ✓ Flexible, Abrasion Resistant
- ✓ Withstand Temperatures up to 1038°C (1990°F)
- ✓ Unexcelled Oven and Furnace Profiling
- ✓ 5 Convenient Styles for Easy Application
- ✓ J, K, E, or N Thermocouple Calibrations

Custom Length and Sizes Available

XCIB Series

Specifications
Wire Gage: 20 gage solid standard limits of error
Insulation: Silica or ceramic (Nextel®) fiber
Overbraiding and Fittings: Inconel 600®
Temperature: 980°C (1800°F) continuous, 1038°C (1990°F) short-term service, depending on thermocouple type
Termination: Ceramic beaded leads with compensated spade lugs, OMEGA® OSTW 220°C (425°F) male connector, or OMEGA® NHXH high-temperature 650°C (1200°F) ceramic male connector

Unique OMEGA family of high-temperature Types J, K, E, or N thermocouples are double-protected with abrasion-resistant Inconel® overbraid with high-temperature fiber insulation. A temperature rating of up to 980°C (1800°F) continuous service and 1038°C (1990°F) short-term service makes these products ideal for many high-temperature measurement applications. They are unexcelled for profiling ovens and furnaces. The 20-gage solid conductor thermocouple wires are insulated with braided ceramic fiber. Over the ceramic fiber is a rugged overbraid of Inconel 600—a tough, high-temperature, high nickel-content alloy. Five convenient styles are available in 1 and 3 m (3 and 10') lengths for high-temperature measurement applications.

Style 1

Style 1 is a grounded junction thermocouple with the Inconel overbraid welded to form a smooth rounded tip for all general purpose applications.

Style 2

Style 2 is a general purpose, bead welded, exposed junction thermocouple.

Style 3

Style 3 is an exposed, bead welded junction thermocouple with an Inconel collar to clamp the probe to a surface, or to secure it into a hole or any fabrication.

Style 4

Style 4 is grounded. It can be bolted to a surface, or the Inconel eye can hook the thermocouple to a conveyor flight. Ungrounded units and special hole sites are available. Contact Sales department for more information.

Style 5

Style 5 has an Inconel air hood to protect the exposed beaded wire junction. This design can be clamped to a surface, hooked to a conveyor flight, or bolted to a surface by using the through hole at the open end of the hood.



To Order Visit omega.com/xcib for Pricing and Details

Model No.	Probe Style	Termination Type	Model No.	Probe Style	Termination Type
XCIB-(*)-1-1-(**)	1	1	XCIB-(*)-4-1-(**)	4	1
XCIB-(*)-1-2-(**)		2	XCIB-(*)-4-2-(**)		2
XCIB-(*)-1-3-(**)		3	XCIB-(*)-4-3-(**)		3
XCIB-(*)-1-4-(**)		4	XCIB-(*)-4-4-(**)		4
XCIB-(*)-1-5-(**)		5	XCIB--(*)-4-5-(**)		5
XCIB-(*)-1-6-(**)		6	XCIB--(*)-4-6-(**)		6
XCIB-(*)-1-7-(**)		7	XCIB--(*)-4-7-(**)		7
XCIB-(*)-2-1-(**)	2	1	XCIB-(*)-5-1-(**)	5	1
XCIB-(*)-2-2-(**)		2	XCIB-(*)-5-2-(**)		2
XCIB-(*)-2-3-(**)		3	XCIB-(*)-5-3-(**)		3
XCIB-(*)-2-4-(**)		4	XCIB-(*)-5-4-(**)		4
XCIB-(*)-2-5-(**)		5	XCIB-(*)-5-5-(**)		5
XCIB-(*)-2-6-(**)		6	XCIB-(*)-5-6-(**)		6
XCIB-(*)-2-7-(**)		7	XCIB-(*)-5-7-(**)		7
XCIB-(*)-3-1-(**)	3	1	* Specify thermocouple Type: J: Iron-Constantan, K: CHROMEALLOY®-ALOMEGA®, E: CHROMEALLOY®-Constantan, N: OMEGALLOY®-NICROSIL-NISIL Use prefix of "CAL-" for assemblies to be supplied with calibration data at specified temperatures. Check Sales department for pricing. ** Specify length in feet: 3' or 10' standard. Price per additional 1', up to over 50' is additional. Note: Available with Nextel insulation. Change "XCIB" in model number to "XSIB". No extra charge.		
XCIB-(*)-3-2-(**)		2			
XCIB-(*)-3-3-(**)		3			
XCIB-(*)-3-4-(**)		4			
XCIB-(*)-3-5-(**)		5			
XCIB-(*)-3-6-(**)		6			
XCIB-(*)-3-7-(**)		7			

For a male straight M8 plug add "M8-S-M" to the model number and additional cost to the price, for a male straight M12 plug add "M12-S-M" to the model number and additional cost to the price. For a male right-angled M8 plug add "M8-R-M" to the model number and additional cost to the price, for a male right-angled M12 plug add "M12-S-M" to the model number and additional cost to the price.

Ordering Example: XCIB-K-1-3-10, XCIB Type K probe, probe style 1 with termination Type 3 m (10') length.

Termination Types

1. Ceramic beaded leads with compensated spade lugs.

2. Type OSTW male standard thermocouple connector to 220°C (425°F).

4. Nextel® insulated leads with compensated spade lugs.

5. Stripped leads.

6. SMPW mini-male connector to 220°C (425°F) max.

7. SHX mini-male ceramic connector to 650°C (1200°F) max.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Omega manufacturer:

Other Similar products are found below :

[DPG409-100DWU](#) [OM-DAQXL-1-NA](#) [CASS-116U-12](#) [DH-1-20-J-12](#) [GG-J-24-SLE-1000](#) [HPC-AU-P](#) [HPC-IR-P](#) [JMQSS-062U-6](#) [KHSS-18G-RSC-12](#) [KHXL-18G-RSC-12](#) [KMQIN-125U-6](#) [KMQXL-125G-12](#) [KMQXL-125U-6](#) [KQSS-18G-6](#) [KQXL-14U-36](#) [KQXL-18G-12](#) [KQXL-18U-12](#) [NB1-CAXL-14U-12](#) [NB3-CAXL-14U-18](#) [P-M-1/10-1/4-6-0-P-3](#) [PX309-015A5V](#) [PX309-1KGI](#) [PX309-10KGV](#) [PX309-100AI](#) [PX309-100AV](#) [PX309-100GI](#) [PX309-100GV](#) [PX309-3KG5V](#) [PX319-V050G5V](#) [PX319-005AI](#) [PX319-050A5V](#) [PX319-050GI](#) [PX319-10KGI](#) [PX319-100GV](#) [PX319-2KGI](#) [PX319-200AV](#) [PX319-200A5V](#) [PX319-300G5V](#) [PX319-5KG5V](#) [PX319-500G5V](#) [PX319-7.5KGI](#) [PX319-7.5KG5V](#) [PX329-1KG5V](#) [PX329-10KGI](#) [PX329-2KGI](#) [PX409-015DWUI](#) [PX409-015VUSBH](#) [PX409-015VV](#) [PX409-050A5V](#) [PX409-10WDWU5V](#)