


Unique Surface/ Insertion Probes

88000 Series



Model No. 88008(*)

Micro-sensor probe, designed for precise measurements of small surface areas, such as transistors and integrated circuits. Small contact surface area of 1.0 x 3.0 mm (0.040 x 0.118") for fast response. 400°C (750°F) max surface temperature.

Note: element not replaceable.

All the probes in this series meet the Standard Limits of Error.

Model No. 88014(*)

Right angle version of the 88013. Fast-response spring-loaded compact tip probe, for measurements to 815°C (1500°F). Surface pad made from 400 series stainless steel. 4.75 mm dia. (0.187") surface area. Not designed for long-term exposure to high temperatures.

Note: element not replaceable.

Model No. 88104(*)

Right angle version of the 88008, with unique lateral spring design and small contact surface area. 400°C (750°F) max surface temperature.

Note: element not replaceable.

Visit us online for dimensions.

All models shown smaller than actual size.

Model No. 88013(*)

Fast-response spring-loaded compact tip probe, for measurements to 815°C (1500°F). Surface pad made from 400 series stainless steel. 4.75 mm diameter. (0.187") surface area. Not designed for long-term exposure to high temperatures. *Note: element not replaceable.*

Model No. 88307(*)

Longer version of the 88306, with 300 mm (12") sheath.

Note: element not replaceable.

Model No. 88305(*)

Measure temperatures in moving air, with drilled sheath to protect the thermocouple, while exposing it to air flow. 0.5 to 20 second response time (depending on air velocity). 480°C (900°F) max service temperature.

Note: element not replaceable.

* Specify Calibration K or E.

Model No. 88306(*)

Pointed tip design, ideal for measuring soft and semi-frozen material, molten plastics and rubbers. 102 mm (4") sheath, with 6 to 20 seconds response time. 500°C (930°F) max service temperature.

Note: element not replaceable.

All models shown smaller than actual size.

Visit us online for dimensions.

Model No. 88308(*)


Specially designed fine hypodermic needle probe, least likely to disturb the surrounding insertion area. 6 to 20 second response time, 205°C (400°F) max service temperature.

Note: element not replaceable.

Model No. 88301(*)

Suitable for measuring internal temperatures of semi-solid materials, such as rubbers, plastics, clay, etc., as well as for liquid measurements. Tapered stainless steel sheath with 480°C (900°F) maximum service temperature.

Note: element not replaceable.



All models supplied with a molded SMP or SMPW subminiature male connector and TAS adaptor.

TAS adaptor

Miniature connector.

Model No. 88009(*)

Thin-body type probe designed to measure the surface of the bottom of narrow gaps or slits, like that of a plate heater. 260°C (500°F) max service temperature.

Note: element not replaceable.

Ordering Example: 88009E, style 88009 probe in Type E thermocouple.

All 88000 series probes are supplied with retractable cable [expands to 1.5 m (5')] and male subminiature connector.

* Specify Calibration:

K: CHROMEGA®-ALOMEGA®
E: CHROMEGA-Constantan

* Specify Calibration K or E.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Omega manufacturer](#):

Other Similar products are found below :

[DPG409-100DWU](#) [OM-DAQXL-1-NA](#) [CASS-116U-12](#) [DH-1-20-J-12](#) [GG-J-24-SLE-1000](#) [HPC-AU-P](#) [HPC-IR-P](#) [JMQSS-062U-6](#) [KHSS-18G-RSC-12](#) [KHXL-18G-RSC-12](#) [KMQIN-125U-6](#) [KMQXL-125G-12](#) [KMQXL-125U-6](#) [KQSS-18G-6](#) [KQXL-14U-36](#) [KQXL-18G-12](#) [KQXL-18U-12](#) [NB1-CAXL-14U-12](#) [NB3-CAXL-14U-18](#) [P-M-1/10-1/4-6-0-P-3](#) [PX309-015A5V](#) [PX309-1KGI](#) [PX309-10KGV](#) [PX309-100AI](#) [PX309-100AV](#) [PX309-100GI](#) [PX309-100GV](#) [PX309-3KG5V](#) [PX319-V050G5V](#) [PX319-005AI](#) [PX319-050A5V](#) [PX319-050GI](#) [PX319-10KGI](#) [PX319-100GV](#) [PX319-2KGI](#) [PX319-200AV](#) [PX319-200A5V](#) [PX319-300G5V](#) [PX319-5KG5V](#) [PX319-500G5V](#) [PX319-7.5KGI](#) [PX319-7.5KG5V](#) [PX329-1KG5V](#) [PX329-10KGI](#) [PX329-2KGI](#) [PX409-015DWUI](#) [PX409-015VUSBH](#) [PX409-015VV](#) [PX409-050A5V](#) [PX409-10WDWU5V](#)