All the probes in this series meet the Standard Limits of Error.

CE OMEGA

Model No. 88304(*)

Flat, leaf-type thermocouple ideal for measuring layers of plywood, plastic, paper and various laminates, with long, 48 cm (19") length. The thermocouple is 0.15 mm (0.006") thick and protected by a 0.8 mm (0.032") PFA jacket, with 50 mm (2") bare at the measurement end. Maximum service temperature is 215°C (420°F). The 88304 is supplied with an OMEGA® OSTW standard-size connector with a TAS-2 standard-to-mini adaptor, and TEC extension cable.

Due to the design and construction of the **88304**, the element is not replaceable.

Model No. 88303(*)

Short leaf-type thermocouple ideal for measuring layers of plywood, plastic, paper and various laminates. The thermocouple is 0.25 mm (0.010") by 0.71 mm (0.028"), protected by a 0.51 mm (0.020") PFA jacket. Maximum service temperature is 215°C (420°F). The 88303 is supplied with an OMEGA® OSTW standard-size connector with a TAS-2 standard-to-mini adaptor, and TEC extension cable.

Due to the design and construction of the **88303**, the element is not replaceable.

Model No. 88309(*)



All models shown actual size.

Flat leaf-type thermocouple ideal for measuring layers of plywood, plastic, paper and various laminates. The small transition allows the probe to be permanently mounted in many installations. Max surface temperature is 210°C (410°F). The 88302 is supplied with an OMEGA® SMPW, TAS-3 adaptor and TEC extension cable.

Due to the design and construction of the **88302**, the element is not replaceable.

Ordering Example: 88302K style 88302 leaf-type probe in Type K thermocouple.

Fast response flat leaf-type thermocouple ideal for measuring layers of plywood, plastic, paper and various laminates. The thermocouple is 100 mm (4") long and 0.05 mm (0.002") thick. Maximum service temperature is 210°C (410°F). The 88309 is supplied with an OMEGA® OSTW, TAS-3 adaptor and TEC extension cable.

Due to the design and construction of the flat leaf-type element, it is not replaceable.

SMPW Miniature Connector

Model No. 88302(*)

SMPW Miniature Connector

0.020" nominal thickness, outside of insulation.

100 (4)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Omega manufacturer:

Other Similar products are found below:

DPG409-100DWU OM-DAQXL-1-NA CASS-116U-12 DH-1-20-J-12 GG-J-24-SLE-1000 HPC-AU-P HPC-IR-P JMQSS-062U-6 KHSS-18G-RSC-12 KHXL-18G-RSC-12 KMQIN-125U-6 KMQXL-125G-12 KMQXL-125U-6 KQSS-18G-6 KQXL-14U-36 KQXL-18G-12 KQXL-18U-12 NB1-CAXL-14U-12 NB3-CAXL-14U-18 P-M-1/10-1/4-6-0-P-3 PX309-015A5V PX309-1KGI PX309-10KGV PX309-100AI PX309-100AV PX309-100GV PX309-3KG5V PX319-V050G5V PX319-005AI PX319-050A5V PX319-050GI PX319-10KGI PX319-10GV PX319-200AV PX319-200AV PX319-200A5V PX319-300G5V PX319-5KG5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-500G5V PX319-300G5V PX319