

Heat Shrink Tubing Medium Wall w/Adhesive 3:1 Shrink Ratio

Description:

NTE's Medium Wall Heat Shrink Tubing is polyolefin based heat–shrinkable tubing suitable for a wide range of telecom and power applications like joints and cable repair. This tubing is ideally suited for aerial, underground and direct burial installation.

Technical Data:

Properties	Test Method	Typical Value	
Physical			
Tensile Strength	ASTM D 638	14 N/mm ²	
Elongation at Break	ASTM D 638	400%	
Longitudinal Change	ASTM D 2671	+0%, -10% Maximum	
Water Absorption	ASTM D 570	< 0.15% Maximum	
Chemical			
Fungus Resistance	ISO 846 Meth. A	Rate I	
Copper Corrosion	ASTM D 2671 B	Good	
Thermal			
Continuous Operating Temperature		−40° to +120°C	
Minimum Shrink Temperature		> +110°C	
Heat Shock (4 Hours at +250°C)	ASTM D 2671	No Dripping, Cracking or Flowing	
Heat Aging (168 Hours at +150°C)	ASTM D 638	Ultimate Elongation 300%	
Low Temperature Flexibility (-55°C)	ASTM D 2671 C	No Cracking (Outer Wall Only)	
Electrical			
Dielectric Strength	ASTM D 2671	17kV/mm	
Volume Resistivity	ASTM D 257	10 @ 14 ohm.cm	

Products Covered:

NTE Catalog Number	Size (inch)	Ratio	I.D. (in mm)		Rec. Wall Thickness
48"			Ехр.	Rec.	(mm)
47–300124–BK	.470	3:1	12	3	1.5
47–300206–BK	.790	3.33:1	20	6	2.5
47–300278–BK	1.060	3.37:1	27	8	2.5
47–304013–BK	1.570	3.07:1	40	13	2.5
47–305117–BK	2.000	3:1	50	17	2.5
47-307222-BK	2.830	3.27:1	72	22	2.5
47–309029–BK	3.540	3.1:1	90	29	2.5
47-312040-BK	4.720	3:1	120	40	2.5

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for nte manufacturer:

Other Similar products are found below:

747 797 868 1724 NEH680M50FE NEHH1.0M450CB NTE48 NTE526A 228A 231 954 2023 47-20848-R 510 R04-11A30-120 04-SLPE3750A 5615 591 7056 NTE5710 7448 NEH.10M50AA NEH2.2M63AA NEH330M35DD NEH33M10AA NEV.22M100AA NEH0006-100 NTE182 NTE528 NTE542 NTE74154 WH20-02-25 04-SCBW25L-BK 04-SCBW32L-BK 04-SCW10C-BK 04-SCBW19L-GR 04-SCW19L-WH 04-SCW19L-OR 04-SCW38L-WH 04-SCBW50L-OR 04-SCBW50L-GR 04-SCW10C-GR 04-SCW10C-OR 04-SCBW32L-GR 04-SCBW32L-WH 04-SCBW32L-OR 04-SCBW6C-WH 04-SCBW6C-GR 04-SCBW6C-OR 04-SCBW25L-GR