


# HEAT SHRINK INSULATED BUTT CONNECTORS

## Specifications

- Waterproof
- Maximum Electrical Rating: 600 Volts
- Shrink Temperature: +150°C
- Operating Temperature: -10° to +105°C
- Terminal Material: Copper Tube
- Plating: Electro Tin Plated
- Insulated Material: Heat Shrinkable Tube




## Ordering Information:

Wire Range AWG / mm <sup>2</sup>	NTE Part Number	Dimensions inch(mm)				Insulated Color
		F	L	D	d	
26 - 24 AWG 0.2 - 0.4mm <sup>2</sup>	76-HIBC26	.472 (12.0)	.945 (24.0)	.082 (2.1)	.047 (1.2)	Transparent
22 - 18 AWG 0.5 - 1.5mm <sup>2</sup>	76-HIBC22	.591 (15.0)	1.457 (37.0)	.177 (4.5)	.063 (1.6)	Red
16 - 14 AWG 1.5-2.5mm <sup>2</sup>	76-HIBC16	.591 (15.0)	1.457 (37.0)	.217 (5.5)	.091 (2.3)	Blue
12 - 10 AWG 4-6mm <sup>2</sup>	76-HIBC12	.591 (15.0)	1.614 (41.0)	.256 (6.5)	.142 (3.6)	Yellow

# HEAT SHRINK INSULATED BUTT CONNECTORS WITH INTERNAL FLUXED SOLDER RING

## Features

- No Crimping Required
- Heat Shrink is Adhesive Lined and Color Coded to Industry Standard Wire Gauges
- Transparent Heat Shrink Sleeve allows for Precise Visual Inspection
- Greater Pull Strength when Compared to PVC or Nylon Insulated Butt Connectors
- Protect Against Corrosion due to a Fully Waterproof Seal
- Rated for 1000V and +125°C with a 2:1 Shrink Ratio



## Specifications

- Waterproof Hot Melt Adhesive
- Maximum Electrical Rating: 1k Volts
- Shrink Temperature: +60°C
- Starting Temperature of Solder Melt: +138°C
- Operating Temperature: -55° to +125°C
- Solder Material: SnBi (42% Tin, 58% Bismuth)
- Terminal Material: Tin
- Plating: None
- Insulated Material: Heat Shrinkable Tube

## Ordering Information:

Wire Range AWG / mm <sup>2</sup>	NTE Part Number	Product Dimensions inch(mm)		Wire Dimensions inch(mm)			Insulated Color
		A (min)	L (max)	B (min)	B (max) C (min)	C (min)	
NEW 26 - 24 AWG 0.2 - 0.4mm <sup>2</sup>	76-HISBC26	.067 (1.7)	1.024 (26.0)	.039 (1.0)	.067 (1.7)	.030 (0.76)	Transparent
NEW 22 - 18 AWG 0.5 - 1.5mm <sup>2</sup>	76-HISBC22	.106 (2.7)	1.575 (40.0)	.055 (1.4)	.106 (2.7)	.047 (1.2)	Red
NEW 16 - 14 AWG 1.5-2.5mm <sup>2</sup>	76-HISBC16	.177 (4.5)	1.575 (40.0)	.090 (2.3)	.177 (4.5)	.079 (2.0)	Blue
NEW 12 - 10 AWG 4-6mm <sup>2</sup>	76-HISBC12	.268 (6.8)	1.614 (41.0)	.146 (3.7)	.268 (6.8)	.134 (3.4)	Yellow

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [nte manufacturer](#):*

Other Similar products are found below :

[747](#) [797](#) [868](#) [1724](#) [NEH680M50FE](#) [NEHH1.0M450CB](#) [NTE48](#) [NTE526A](#) [228A](#) [231](#) [954](#) [2023](#) [47-20848-R](#) [510](#) [R04-11A30-120](#) [04-SLPE3750A](#) [5615](#) [591](#) [7056](#) [NTE5710](#) [7448](#) [NEH.10M50AA](#) [NEH2.2M63AA](#) [NEH330M35DD](#) [NEH33M10AA](#) [NEV.22M100AA](#) [TP0006-100](#) [NTE182](#) [NTE528](#) [NTE542](#) [NTE74154](#) [WH20-02-25](#) [04-SCBW25L-BK](#) [04-SCBW32L-BK](#) [04-SCW10C-BK](#) [04-SCBW19L-GR](#) [04-SCW19L-WH](#) [04-SCW19L-OR](#) [04-SCW38L-WH](#) [04-SCBW50L-OR](#) [04-SCBW50L-GR](#) [04-SCW10C-GR](#) [04-SCW10C-OR](#) [04-SCBW32L-GR](#) [04-SCBW32L-WH](#) [04-SCBW32L-OR](#) [04-SCBW6C-WH](#) [04-SCBW6C-GR](#) [04-SCBW6C-OR](#) [04-SCBW25L-GR](#)