

## Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Tool for processing ferrules according to DIN 46228-4, 0.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup>, equipped with pressure lock, cutting, stripping, twisting, and crimping unit, with three magazines including a strip each of ferrules from 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, packaged in a robust plastic case

### Why buy this product

- ✔ Integrated pressure lock ensures consistently high-quality crimping
- ✔ Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- ✔ Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- ✔ Robust and durable due to use of resistant plastics and annealed metals
- ✔ Visualized process flows directly on the pliers simplify operation



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 042398
GTIN	4055626042398
Weight per Piece (excluding packing)	727.700 g
Custom tariff number	82032000
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	180 mm
Width (a)	31.5 mm
Height	100 mm

#### General

Compression	Indent crimp
-------------	--------------

# Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

## Technical data

### General

Type of contact	Ferrules
Min. AWG, flexible, multi-strand	14
AWG max., flexible, multi-strand	20
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	20
AWG max	14
Maximum stripping length	11 mm
Weight	600 g

## Classifications

### eCl@ss

eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 8.0	21043811
eCl@ss 9.0	21043811

### ETIM

ETIM 4.0	EC000168
ETIM 5.0	EC000168
ETIM 6.0	EC000168

### UNSPSC

UNSPSC 13.2	27111518
-------------	----------

## Accessories

### Accessories

#### Connector

Ferrule - Al 0,5-8 WH S1 - 1200104



Taped ferrules, 0.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, white, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

## Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

### Accessories

#### Ferrule - AI 0,75- 8 GY S1 - 1200105



Taped ferrules, 0.75 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, gray, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

---

#### Ferrule - AI 1,0-8 RD S1 - 1200106



Taped ferrules, 1.0 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, red, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

---

#### Ferrule - AI 1,5-8 BK S1 - 1200107



Taped ferrules, 1.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, black, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

---

#### Ferrule - AI 2,5-8 BU S1 - 1200108



Taped ferrules, 2.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, blue, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 40 sleeves per strip.

---

#### Ferrule - AI 0,75- 8 BU S1 - 1200163



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: blue, number of strips: 10, number of sleeves per strip: 50

---

## Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

### Accessories

Ferrule - Al 2,5-8 GY S1 - 1200164



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: gray, number of strips: 10, number of sleeves per strip: 40

---

### Magazine

Magazine - CRIMPFOX 4 IN 1/MAG - 1200103



Ferrule magazine for CRIMPFOX 4 IN 1, for ferrules with insulating collars from 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, with a length of 8 mm

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [phoenix contact manufacturer](#):*

Other Similar products are found below :

[1203259](#) [3240366](#) [1893300](#) [1212619](#) [1927221](#) [1936102](#) [1730573](#) [3240367](#) [1014246](#) [1014236](#) [1014240](#) [1014290](#) [1014293](#) [1806193](#)  
[1823655](#) [1912825](#) [1842254](#) [1768260](#) [1716373](#) [1648030](#) [1579051](#) [1014235](#) [1014239](#) [1014229](#) [1212378](#) [2800744](#) [2867076](#) [3006564](#)  
[2800741](#) [5146480](#) [1582539](#) [1623633](#) [1507793](#) [3025587](#) [3069708](#) [1431461](#) [1586976](#) [0311647](#) [1460160](#) [1771338](#) [3048387](#) [2814605](#)  
[0309086](#) [1513716](#) [3035684](#) [5451417](#) [0202219](#) [1647747](#) [1730667](#) [1709267](#)