



5419 Low Static Polyimide Film Tape

Product Data Sheet

Updated : March 1996
Supersedes : November 1993

Product Description A translucent polyimide film backed silicone adhesive tape with unique and extremely low electrostatic discharge properties for gold edge protection during wave soldering of printed circuit boards.

Physical Properties
Not for specification purposes

Adhesive Type	Silicone	
Backing	Polyimide	
Thickness (ASTM D-3652)	70 µm	
Backing Thickness	30 µm	
Tape Colour	Gold	
Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

Performance Characteristics
Not for specification purposes

Adhesion to Stainless Steel <small>ASTM D-3330</small>	2.2 N/10mm	
Tensile Strength <small>ASTM D-3759</small>	577.8 N/10mm	
Elongation at Break <small>ASTM D-3759</small>	60 %	
Temperature Range Maximum Minimum	260 °C -73 °C	
Dielectric Strength	7000 volts	
Insulation Resistance	>1*10 ⁶ ohms	

Date : March 1996
5419 Low Static Polyimide
Film Tape

Performance Characteristics Not for specification purposes	Static Charge	(Measured at 50% RH, 21° in an ESD Controlled Environment.	
	Removal from roll	< 150 volts	
	Removal from PCB	< 50 volts	

Additional Product Information

5419 tape employs a proprietary technology that results in extremely low electrostatic discharge at unwind and removal from the PCB. Conventional polyimide tapes can typically generate over 10,000 volts during use which can damage board mounted electronic components.

5419 tape overcomes this problem without any of the typical drawbacks of conventional "anti-static" or "static-free" tapes (e.g. variable adhesion and opaqueness). At room temperature the properties of polyimide and polyester film are similar.

However, as the temperature increases or decreases, to properties of the polyimide film are less affected than polyester. Polyimide film does not soften at elevated temperatures, thus, the film provides an excellent release surface at elevated temperatures.

Application Techniques

Best results are attained when applied to a clean, dry and non dusty surface above 0°C.

To improve adhesion ensure firm and even application pressure is applied.

Applications

Mask for printed circuit boards during wave solder or solder dip process.

Used as release surface in fabrication of parts cured at elevated temperatures.

Features

Polyimide Film

Silicone Adhesive

Low Static

Advantages

Dimensionally stable at high temperatures.

Flame retardant and chemical resistant.

High temperature performance reduces adhesive transfer.

Virtually eliminates circuit board degradation due to electrostatic discharge.

Benefits

Helps promote high productivity.

Protect surfaces, helping reduce replacement.

Helps promote high productivity.

Reduces costly board waste due to component failure.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Specialty Tapes & Adhesives

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
3M House,
28 Great Jackson Street,
Manchester,
M15 4PA

Customer Service :
Tel 0161 236 8500
Fax 0161 237 1105

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

Customer Service :
Tel (01) 280 3555
Fax (01) 280 3509

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [3m manufacturer](#):

Other Similar products are found below :

[SC401U](#) [98-0003-3071-6](#) [00-054007-70220-7](#) [00-054007-34717-0](#) [021200-40230](#) [6840-2X50-GRAY](#) [D2550-6002-AR](#) [701-W](#) [7993MP-2CIRCLE-100](#) [FDV14-187C](#) [8124/14](#) [812510-100](#) [8125/17](#) [813216](#) [8204-3LFM](#) [8425-8](#) [MNG14BCX](#) [FP301-1-6"-Clear](#) [FV14-6C](#) [920102-01-25-R](#) [923835-BK-C](#) [927739-40](#) [929835-01-28-RK](#) [929836-09-16](#) [929974-01-40-R](#) [951240-2520-AR-PR](#) [960X/980X](#) [98-0003-3075-7](#) [HF36564-100](#) [HF625/26-30](#) [1/2-5-5430](#) [1/2-5-850S](#) [1/2-5-3431](#) [12X12-6-4056B](#) [12X12-6-433](#) [12X12-6-4930](#) [13-500-NB](#) [14526-EZ5B-300-02C](#) [1-4-4658F](#) [14520-EZAB-300-0EC](#) [DSTK9013-3420](#) [DSTK9015-3402](#) [14T50-SZWB-100-0NC](#) [152244-0110-GB](#) [1-5-3437](#) [1-5-4496W](#) [1-5-4943F](#) [1-5-363](#) [1-5-5451](#) [1-5-421](#)