Crocodile Clip with 4mm Socket






Features

- High Reliability
- High Stability
- · Economical and practical

Specifications

Body Material	: Brass
Insulation Material	: PA
Contact Resistance	: ≤0.005Ω
Surface Coating	: Nickel Plated
Insulating Resistance	: ≥500MΩ
Rated Voltage Current	: 30V AC - 60V DC/ Max. 15A

Diagram



Part Number Table

Description	Part Number
Crocodile Clip, Insulated, 4mm SKT, Red	76-1205
Crocodile Clip, Insulated, 4mm SKT, Black	76-1210

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com



X-ON Electronics

Authorized Distributor

Click to view similar products for Tenma manufacturer.

Other Similar products are found below :

 BEBKQRT
 7210160727770A
 722630
 76090
 76097
 76300
 76350
 761444
 76020
 21685

 7213300
 7213768
 7214058
 7214316
 7214320
 7214322
 ST5C
 76270
 BECKKRT

 BECKMRT
 7210179727770A
 727635
 76082
 761662
 76021