# EPIC® MH 8.0mm Contacts

High flexibility by the use of any combination of inserts in one connector

### Info
Stamped gold plated contacts with 0.8mm diameter for D-Sub inserts



Voltage

Wind Energy

Rail

Mechanical and plant engineering

Automation &amp; fältinstallation

Flame-retardant

### Benefits
Crimp connection for permanent vibration proof contact
EPIC® MH system is mateable with the market standard

### Application range
Mechanical engineering
Robot-building
Plant engineering
Renewable energy
Railway applications / vehicle construction

# EPIC® MH 8.0mm Contacts

## Technical Data

| | |
|---|---|
| Classification: | ETIM 5.0 Class-ID: EC000796 |
| | ETIM 5.0 Class-Description: Contact for industrial connectors |
| Contact resistance: | < 5 mOhm |
| Termination methods: | Crimp termination: 10 mm² ... 35 mm² |
| Stripping length (mm): | 18 |
| Cycle of mechanical operation: | 500 |

## Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

| Article number | Article description | Contact type | Connec |
|---|---|---|---|
| EPIC® MH D=8.0 contacts | | | |
| 44423242 | EPIC® MH SCEM AG 10sqmm D=8.0 | male | 10 |
| 44423246 | EPIC® MH BCEG AU 0.09 - 0.25sqmm D=1.0 | female | 10 |
| 44423243 | EPIC® MH SCEM AG 16sqmm D=8.0 | male | 16 |
| 44423247 | EPIC® MH BCEM AG 16sqmm D=8.0 | female | 16 |
| 44423244 | EPIC® MH SCEM AG 25sqmm D=8.0 | male | 25 |
| 44423248 | EPIC® MH BCEM AG 25sqmm D=8.0 | female | 25 |
| 44423245 | EPIC® MH SCEM AG 35sqmm D=8.0 | male | 35 |
| 44423249 | EPIC® MH BCEM AG 35sqmm D=8.0 | female | 35 |

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* epic *manufacturer:*

Other Similar products are found below :

44420040 + 73002716  19426500  72004000 + 73018000  13.1623  11161000  11.1610  9198+00022030  72004000 + 73002756  72000010  10.5310  10.4264+10.4310  72040010  HA4-FK-TE-SM-M-M20  10.4310  10.1270+10.1970+12.9545  10.4220+10.4320  10.4265+10.4235+10.4200+10.4210  10121000+10196000+12954500  10.0720  44420037 + 73002752  10102000  10.4264  8990+00022030  72004000 + 73002716  10.4861  44420037 + 73018000  10.1210+10.1960+12.9545  10.4881  10.0220+10.0030+10.1900+10.1910+12.9544  10431000  10.1920  44420037 + 73028500  13.1622  44420037 + 73002716  10.1900