

# Flexible AS-I BUS Multicore Cable **pro-POWER**



**RoHS  
Compliant**

## Application

This AS-I fieldbus multicore cable facilitates simultaneous data and energy transmission. Application in signalling circuits, in production facilities and machine tools. Sheathed with a flame retardant Low Smoke Zero Halogen.

## Characteristics

Voltage Rating	: 300V
Test Voltage	: 2kV
Temperature Rating	: Fixed: -40°C to +105°C Flexed: -30°C to +105°C
Minimum Bending Radius	: Fixed: 12 × overall diameter Flexed: 24 × overall diameter


## Cable Standards

DIN EN 60228, VDE 0295, IEC 60228, IEC 60811-2-1, IEC 60707



## UK Laboratory Tested

This product is subject to the Quality Assurance protocols of The Cable Lab®, a UKAS accredited ISO 17025 cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



## Regulatory Compliance

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



## Construction

### Conductor

Class 6 stranded tinned copper wires

### Insulation

TPE (Thermoplastic Elastomer)

### Sheath

TPE (Thermoplastic Elastomer)

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)

**pro-POWER**

# Flexible AS-I BUS Multicore Cable **pro-POWER**

## Core Identification

Blue and Brown

## Sheath Colour

Yellow and Black

## Dimensions

Part Number	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Nominal Overall Diameter mm
PP001549	2	1.5	2.5
PP001550			

## Electrical Characteristics at 20°C

Max. Conductor Resistance mΩ/m	Capacitance at 167kHz pF/m	Inductance at 167kHz nH/m	Impedance at 167kHz Ω
13.7	35 to 45	520 to 700	70 to 140

## Part Number Table

Description	Nominal Cross Sectional Area mm <sup>2</sup>	Sheath Colour	Reel Length	Part Number
Flexible AS-I BUS Multicore Cable	1.5	Yellow	100m	PP001549
		Black		PP001550

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)

**pro-POWER**

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)